



120V FLEX LED STRIP LIGHT SERIES

- Direct to Line Voltage Power, No Separate Drivers Required
- Wet Location & IP65 Rated for Indoor and Outdoor Applications
- Maximum Continuous Run Length of 164 feet
- Made to Order and Assembled at Specific Lengths, Ready to Wire and Install
- Available in Two Versions:
 - 120V Flex LED for Indirect View
 - 120V Flex Neon LED for Direct View Applications
- Unique Circuit Design Prevents Overheating, Extending Projected Life

120V FLEX LED STRIP LIGHT SERIES

TLTAC and TLNEAC Flex LED Strip Lights are custom made to order. Allow 2 – 4 weeks lead time. Project orders may need additional lead time. These products are **NOT FIELD CUTTABLE**. Doing so voids agency certification and warranty.

TLTAC: 120V FLEX LED STRIP LIGHT



- Flexible, line voltage, wet location, LED accent lighting system
- Energy efficient illumination for indoor and outdoor indirect view applications including architectural enhancements, outdoor steps or changes in elevation, coves, etc.
- Max continuous run length of 164 feet orderable in 4-inch increments, no driver needed
- Delivering 284 lumens per foot at 3000K, 90+ CRI

Tapelight Series	Power Cord	Version	Input	End	Color Temp	Nominal Length ¹	Add'l Length
TLTAC - 120VAC FlexLED Strip Light	H - Hardwire P - Cord & Plug	1 - 18 LEDs/Ft	S - Sealed	S - Sealed	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	XXX - Length in Feet	Leave Blank/ No Add'l Inches 4 - 4 Add'l Inches 8 - 8 Add'l Inches

1. Available in 4" increments (max. 164'). Example: 10ft 4in is entered as "010-4", 10ft is entered as "010"



Mounting Accessories (Sold Separately)

- TLACACMC** - PVC Mounting Clip Set; 10 Clips per Set
- TLACACS6** - 6Ft Aluminum Mounting Channel

TLNEAC: 120V FLEX NEON LED STRIP LIGHT



- Flexible, line voltage, wet location, dot-free Neon look LED lighting system
- Energy efficient accent illumination for indoor and outdoor direct view applications including architectural enhancements, outdoor steps or changes in elevation, coves, etc.
- Max continuous run length of 164 feet orderable in 12-inch increments, no driver needed
- Delivering 53 lumens per foot at 3000K, 90+ CRI

Tapelight Series	Power Cord	Version	Input	End	Color Temp	Nominal Length ¹
TLNEAC - 120VAC Neon Linear Flex	H - Hardwire P - Cord & Plug	1 - 36 LEDs/Ft	S - Sealed	S - Sealed	27K - 2700K 30K - 3000K 35K - 3500K 40K - 4000K	AMB - Amber BLU - Blue GRN - Green RED - Red XXX - Length in Feet

1. Available in 1ft increments (max. 164') Example: 10ft is entered as "010"



Mounting Accessories (Sold Separately)

- TLNEACACMC** - Stainless Steel Mounting Clip Set
10 Clips per Set
- TLNEACACS6** - 6Ft Aluminum Mounting Channel