

INSTALLATION INSTRUCTIONS | Gallery M Canopy Mount Luminaire: CTL93 C

The important safeguards and instructions here are not meant to cover all possible conditions and situations that may occur.

IMPORTANT SAFETY INSTRUCTIONS:

- **WARNING: RISK OF FIRE AND ELECTROCUTION**
- **WARNING: TO AVOID FIRE, SHOCK OR DEATH**, disconnect power at circuit breaker before installing or servicing device
- **READ AND SAVE THESE INSTRUCTIONS FOR LATER USE**
- Product should be installed by an electrician
- All electrical connections must be in accordance with local and National Electrical Code (NEC) standards. If you are unfamiliar with proper electrical wiring connections, consult an electrician.
- Product must be grounded to avoid potential electric shock and any other potential hazards
- Product must be mounted in locations and at heights and in a manner consistent with its intended use, in compliance with National Electrical Code and local codes and where it will not readily be subject to tampering by unauthorized personnel
- To prevent damage to the wiring, do not expose wiring to edges of sheet metal or other sharp objects
- Wear rubber soled shoes and work on a sturdy wooden or non-conductive ladder
- Ground the fixture to avoid potential electric shock and to ensure reliable starting
- Double check all connections and screws, ensuring they are tight and correct
- **WARNING:** Risk of fire; most dwellings built before 1985 have supply wire rated at 60°C. Supply conductors (power wires) connecting the luminaire must be rated at minimum of 90°C.
- **WARNING:** Risk of burns. Lamps are extremely hot when lit. Allow lamps to cool down in temperature before handling.
- Installing contrary to instructions may cause unsafe conditions
- If the product has any visible damage do not install it
- Call the Technical Support department at ConTech Lighting with any installation questions: 847.559.5500

INSTALLATION |

Prior to installation, ensure a 4-inch Round or Square (with a Square-to-Round Junction Box Cover Plate) Junction Box is properly mounted to the ceiling structure.

1. Loosen the two (2) Mounting Screws on the Canopy and remove the Mounting Bracket from the Canopy
2. Securely attach the Mounting Bracket to the Junction Box
3. Verify that the primary voltage matches the voltage range of the Driver
4. Position the Canopy/Luminaire assembly close to the Mounting Bracket
5. Connect the leads from the Junction Box to the leads of the Luminaire: Black-to-Black, White-to-White and Green-to-Ground
6. If using 0-10V Dimming, connect Purple and Pink/Grey wires per the Dimmer instructions; otherwise, use wire connectors to cap these wires individually
7. Carefully tuck excess wires and connectors into the Junction Box while positioning the Canopy in place
8. Tighten Mounting Screws to complete assembly

