


OTL93 SERIES | Gallery M Track Luminaire with 0-10V Dimming Track System Adapter



High performance track luminaire delivering high outputs and superior beam control

- Clean aesthetics, simple cylinder form
- Multiple beam distributions
- Delivering up to 3700 Lumens
- Consistent color rendering



	OTL931	OTL932	OTL933	OTL934	OTL935
WATTAGE	10W	14W	19W	28W	35W
LUMEN OUTPUT ¹ BY BEAM SPREAD					
Narrow Spot (12°)	1058 Lm	1424 Lm	N/A	N/A	N/A
Spot (15°)	1110 Lm	1536 Lm	2108 Lm	2768 Lm	N/A
Narrow Flood (22°)	981 lm	1374 Lm	1914 Lm	2587 lm	3260 Lm
Medium Flood (35°)	1118 Lm	1566 Lm	2182 Lm	2949 Lm	3716 Lm
Flood (52°)	1124 Lm	1574 Lm	2193 lm	2964 Lm	3735 Lm
Wide Flood (79°)	1046 Lm	1464 Lm	2040 Lm	2758 Lm	3475 Lm
COLOR TEMPERATURE	2700K / 3000K / 3500K / 4000K				
CRI	83 (80min) / 90+				
FINISHES	Matte Black / Matte White / Matte Silver				
DRIVER INPUT VOLTAGE	120V or 277V, 50/60Hz				
DIMMING TYPE	0-10V Dimming				
COMPATIBILITY	Compatible with ConTech Lighting O2CD 0-10V Dimming Track System				
LISTINGS	cCSAus Certified for use in the U.S. and Canada; Suitable for Dry Locations				
WARRANTY	Five (5) year replacement after date of purchase				
SYSTEM RATING	50,000 Hours @ 70% Lumen Maintenance				

1. Approximate lumen output based on 3000K performance; see photometric test results for additional information

OTL93 SERIES | Gallery M Track Luminaire with 0-10V Dimming Track System Adapter

ORDERING INFORMATION

Example Order: OTL932SP3K12D2-P

LED Series	Beam Option	CCT/CRI	Driver ⁴	Finish
OTL931 10W	NS² Narrow Spot: 12° Beam / 21° Field	80+ CRI	12D2 120V 0-10V Dimming	B Matte Black
OTL932 14W	SP³ Spot: 15° Beam / 31° Field	27K 2700K		P Matte White
OTL933 19W	NF Narrow Flood: 22° Beam / 45° Field	3K 3000K	27D2 277V 0-10V Dimming	S Matte Silver
OTL934 28W	MF Medium Flood: 35° Beam / 56° Field	35K 3500K		
OTL935 35W	FL Flood: 52° Beam / 62° Field	4K 4000K		
	WF Wide Flood: 79° Beam / 101° Field	4KC 4000K		


2. Narrow Spot (NS) Beam is only available for Series 1 (10W) and Series 2 (14W)

3. Spot (SP) Beam is only available for Series 1 (10W) through Series 4 (28W)

4. Selected Driver Voltage MUST match Track System Voltage


ACCESSORY & REPLACEMENT OPTIC ORDERING INFORMATION

Each Gallery M Luminaire may hold up to two (2) pieces of Media **OR** one (1) Snoot or Barn Door Assembly plus one (1) piece of Media



Snoot with Optional Cross Blades

Exterior painted per finish selection: Black (B), White (P) or Silver (S). Interior and Cross Blades are always Black.



Barn Doors

Black finish. Barn Doors may hold one LF18 Lens or LA-35 Honeycomb Louver.



Honeycomb Louver

Black finish

Accessory
FA-93 Snoot with optional Cross Blades

Finish
B Matte Black
P Matte White
S Matte Silver

Accessory
BD93 Barn Doors

Finish
B Matte Black

Accessory
FA-16-60MM 2-3/8-In. Black Honeycomb Louver
LA-35 3-1/16-In. Black Honeycomb Louver for use within Barn Doors only



Tempered Glass Filters and Lenses

1/8-Inch Thick, typ.

Accessory
LF16 Tempered Glass Filters and Lenses
LF18 Tempered Glass Filters and Lenses for use within Barn Doors only

Finish	
C	Clear
SL	Soft Light
SOL	Solite
LS	Linear Spread
A	Amber
B	Blue
LB	Light Blue
G	Green
R	Red
RO	Rose
Y	Yellow

Size
60MM 2-3/8-Inch
Leave Blank
3-1/16-Inch
LF18 Series for use within Barn Doors only

Replacement Optics
CTL930PT-NS⁵ Narrow Spot Replacement 12° Beam / 21° Field
CTL930PT-SP⁶ Spot Replacement 15° Beam / 31° Field
CTL930PT-NF Narrow Flood Replacement 22° Beam / 45° Field
CTL930PT-MF Medium Flood Replacement 35° Beam / 56° Field
CTL930PT-FL Flood Replacement 52° Beam / 62° Field
CTL930PT-WF Wide Flood Replacement 79° Beam / 101° Field

5. Narrow Spot (CTL930PT-NS) Optic is only for use on luminaires originally ordered with NS Optic

6. Spot (CTL930PT-SP) Optic is only for use on luminaires originally ordered with SP Optic

OTL93 SERIES | Gallery M Track Luminaire with 0-10V Dimming Track System Adapter

PRODUCT SPECIFICATIONS

PERFORMANCE SUMMARY

- 2700K, 3000K, 3500K and 4000K CCTs; 80 CRI min., 83 typical; high CRI of 90+ available
- Excellent fixture-to-fixture color consistency with a 2-step MacAdam Ellipse tolerance
- Precise beam control ensures that even at lower aiming angles the luminaire is glare free and quiet in the ceiling
- Full collection of accessories available to produce a myriad of filtering and framing effects
- 120V or 277V 0-10V Dimming. For dimmer compatibility and performance, refer to the Dimming Specifications below.

CONSTRUCTION

- A revolutionary track head with superior optics designed to bring theatre grade beam control to traditional gallery and commercial track heads
- Constructed of die-cast aluminum, the cylindrical body provides thermal management for the luminaire
- An integrated adapter suitable for use with the ConTech O2CD 0-10V Dimming Track System is included
- Locking mechanisms for Tilt (0° to 91°) and Rotation (365°)

- Six (6) Beam Distributions available: 12° Narrow Spot, 15° Spot, 22° Narrow Flood, 35° Medium Flood, 51° Flood, and 79° Wide Flood
- Narrow Spot and Spot Beam configurations utilize smaller LES LEDs to achieve beams and may not be used in higher wattage options (see Ordering Information for details)
- Optics are field interchangeable (with restrictions) and provide smooth, striation-free beams
- Luminaire may accept up to two (2) pieces of media (Lens or Louver), one (1) Snoot/Barn Door Assembly plus one (1) piece of media (Lens or Louver). Consult ordering information for proper combinations and sizes.

NOTE: Luminaire may hold one (1) LF16 60MM Series Lens or FA-16-60MM Louver;

Barn Doors may hold one LF18 Series Lens or LA-35 Louver

- Integral ON/OFF switch and track polarity indicator are standard
- Fixture weight: 3 LBS

FIXTURE COMPATIBILITY

- ConTech OTL Track Luminaires are compatible with the ConTech Lighting O2CD 0-10V Dimming Track System

DIMMING SPECIFICATIONS

- 0-10V Dimming may be used for 120V or 277V powered Luminaires by delivering a separate controlled DC voltage signal which adjusts the light output.

0-10V COMPATIBLE DIMMERS			
MANUFACTURER	PRODUCT	MODEL	LIGHT OUTPUT
Leviton	IlumaTech	IP710-DL	5% to 100%
Lutron	Diva	DVTV	5% to 100%
Lutron	Nova	NFTV	5% to 100%

NOTES

1. If light is measured, then the dimming range is based on light output. If light is not measured, then the dimming range is based on the percentage of output current.
2. Testing was performed with a single fixture connected to dimmer.
3. Testing has been performed on these dimmers, but this does not imply any warranty of compatibility.
4. Dimming performance can be influenced by different loads, as well as variations in dimmer switches within the same model.
5. Dimmer maximum load rating with LED may differ from published traditional source dimmer ratings. Consult manufacturer for maximum dimmer information.
6. Consult factory for additional dimming information.



CTL93 SERIES | Gallery M Track Luminaire Standard Luminous Photometry

CTL932NS3KD: 14W, 3000K, 83 CRI, NARROW SPOT BEAM

Test No. G25072304

Fixture Delivered Lumens: 1423.61
Total Watts@120V: 14.7
Lumens Per Watt: 96.84
Center Beam Candle Power: 29580
Beam Distribution: 11.6°
Spacing Criterion: 0.19
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

Intensity Distribution		
DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	1848.8	0.8
6 FT	821.7	1.2
8 FT	462.2	1.6
10 FT	295.8	2.0
12 FT	205.4	2.4
14 FT	150.9	2.9



NARROW SPOT BEAM OUTPUT MULTIPLIERS

10W



0.74

CTL934SP3KD: 28W, 3000K, 83 CRI, SPOT BEAM

Test No. G25082504

Fixture Delivered Lumens: 2767.5
Total Watts@120V: 28.7
Lumens Per Watt: 96.43
Center Beam Candle Power: 26608
Beam Distribution: 14.8°
Spacing Criterion: 0.27
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

Intensity Distribution		
DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	1663.0	1.0
6 FT	739.1	1.6
8 FT	415.8	2.1
10 FT	266.1	2.6
12 FT	184.8	3.1
14 FT	135.8	3.6



SPOT BEAM OUTPUT MULTIPLIERS

10W

14W

19W

0.40

0.56

0.76

1. Accuracy of Rendering Colors 2. Color Appearance of Light Source 3. Dependent on Surrounding Temperatures 4. Colors Present within the Light Source

PHOTOMETRIC MULTIPLICATION FACTORS

Lumen output values fluctuate based on Color Temperature (CCT), Color Rendering Index (CRI), and Luminaire Wattage/Output. To estimate lumen output of the various options, multiply the 3000K standard CRI results by the following:

CCT MULTIPLIERS		
CCT	STANDARD CRI	HIGH (90+) CRI
2700K	0.98	0.81
3000K	1.00	0.85
3500K	1.01	0.86
4000K	1.02	0.89



CTL93 SERIES | Gallery M Track Luminaire Standard Luminous Photometry

CTL935NF3KD: 35W, 3000K, 83 CRI, NARROW FLOOD BEAM

Test No. G25071703

Fixture Delivered Lumens: 3259.7
Total Watts@120V: 35.4
Lumens Per Watt: 92.08
Center Beam Candle Power: 17020
Beam Distribution: 21.6°
Spacing Criterion: 0.37
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	1063.7	1.5
6 FT	472.8	2.3
8 FT	265.9	3.1
10 FT	170.2	3.8
12 FT	118.2	4.6
14 FT	86.8	5.4





CTL935MF3KD: 35W, 3000K, 83 CRI, MEDIUM FLOOD BEAM

Test No. G25071702

Fixture Delivered Lumens: 3715.7
Total Watts@120V: 35.4
Lumens Per Watt: 104.96
Center Beam Candle Power: 9897
Beam Distribution: 35.2°
Spacing Criterion: 0.55
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	618.6	2.5
6 FT	274.9	3.8
8 FT	154.6	5.1
10 FT	99.0	6.3
12 FT	68.7	7.6
14 FT	50.5	8.9





CTL935FL3KD: 35W, 3000K, 83 CRI, FLOOD BEAM

Test No. G25071701

Fixture Delivered Lumens: 3735.1
Total Watts@120V: 35.4
Lumens Per Watt: 105.51
Center Beam Candle Power: 6137
Beam Distribution: 51.8°
Spacing Criterion: 0.71
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	383.5	3.9
6 FT	170.5	5.8
8 FT	95.9	7.8
10 FT	61.4	9.7
12 FT	42.6	11.6
14 FT	31.3	13.6





CTL934SP3KD: 35W, 3000K, 83 CRI, WIDE FLOOD BEAM

Test No. G25091601

Fixture Delivered Lumens: 3474.6
Total Watts@120V: 35.1
Lumens Per Watt: 99.00
Center Beam Candle Power: 2347
Beam Distribution: 79.4°
Spacing Criterion: 1.13
Color Rendering Index (CRI)¹: 82.8
Color Temperature (CCT)²: 3004K
Designed for 50,000 Hour Lamp Life³

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
4 FT	146.7	6.7
6 FT	65.2	10.0
8 FT	36.7	13.3
10 FT	23.5	16.6
12 FT	16.3	19.9
14 FT	12.0	23.3



1. Accuracy of Rendering Colors 2. Color Appearance of Light Source 3. Dependent on Surrounding Temperatures 4. Colors Present within the Light Source

PHOTOMETRIC MULTIPLICATION FACTORS

Lumen output values fluctuate based on Color Temperature (CCT), Color Rendering Index (CRI), and Luminaire Wattage/Output. To estimate lumen output of the various options, multiply the 3000K standard CRI results by the following:

CCT MULTIPLIERS		
CCT	STANDARD CRI	HIGH (90+) CRI
2700K	0.98	0.81
3000K	1.00	0.85
3500K	1.01	0.86
4000K	1.02	0.89

OUTPUT MULTIPLIERS			
10W	14W	19W	28W
0.30	0.42	0.59	0.79



CTL93 SERIES

| Gallery M Track Luminaire Standard Luminus Photometry

TM-30 DATA: CTL935MF3KD

ANSI/IES TM-30-18 Color Rendition Report Test No. S21072001

Colors are for visual orientation purposes only



HUE BIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
HUE SHIFT	0%	7%	10%	6%	3%	-2%	-6%	-1%	3%	8%	11%	2%	-8%	-16%	-13%	-14%
R _f VALUE	80	82	80	91	94	94	88	94	90	86	84	87	88	80	79	78