

INSTALLATION PROCEDURES:

1. Feed cable length through Cable Coupler so that starter crimp seats within.
2. Attach Cable Coupler to 1/4-20 toggle bolt assembly/ceiling plate, leaving cable length to hang free.
3. Prepare Con-Tech track by removing the plastic grommets (two per 2', 4', 6' track section, 3 per 8' track section, 4 per 12' track section). Pass threaded portion of the Cable Holder through mounting hole and firmly lock with nut provided. Use two cable assemblies to support each 2', 4', 6' track section; three per 8' track section; and four per 12' track section.

ALTERNATE MOUNTING FOR 8' AND 12' TRACK SECTIONS:

Drill two 1/4" holes on 4' centers through the back of the track. Care must be taken to center the holes in the track width. When 4' centers are maintained, two cables may be used for each 8' track section and three for each 12' track section.

4. Lift track to desired height and pass loose cable end through small hole in the top of the Cable Holder. Cable will pass through and lock in any stopped position. Determine finished mounting height and level. If this point is exceeded and you are required to shift the Cable Holder upwards, support the track and release lock by depressing small release button at the top of the Cable Holder, draw cable through until the desired position is achieved.
5. Cut off excess cable protruding below lock nut.

IMPORTANT SAFETY INSTRUCTIONS:

- Read all the instructions before installation. Save instructions for later use.
- Turn off the power at fuse or circuit breaker box before installation or maintenance work.
- Wear rubber soled shoes and work on a sturdy wooden or non-conductive ladder.
- Product must be mounted in locations and at heights in compliance with National Electrical Code and local building codes. For indoor use only.
- Do not exceed the nominal supply voltage or amperage ratings.
- Installing contrary to instructions may cause unsafe conditions.
- **Warning:** Risk of fire. Most dwellings built before 1985 have supply wire rated at 60°C. Consult a qualified electrician before installation.
- Avoid hazards to children: account for all parts and properly dispose of all packing materials.
- Call the Technical Support department at ConTech Lighting with any installation questions.

PARTS:

- (1) Cable Coupler (threaded for 1/4-20 stud)
- (1) Cable Holder
- (1) Length of 1/16" Galvanized Cable with starting crimp
- (1) 1/4-20 Toggle Bolt Assembly (Use 3/4" ceiling hole)
- (1) Ceiling Plate

