

DATE

PROJECT

TYPE

# LVR16 SERIES | Trims for 4-Inch Low Voltage Downlights

- All 4-inch Low Voltage Trims are cCSAus Certified and Suitable for Damp Locations; only Shower Trims are Wet Location Listed
- Max Lamp: 50W 12V MR-16 lamp, GU5.3 base, unless noted
- All Trims have White Trim finish unless specified
- For Trims designed for use with MR16 Lamps, ConTech Lighting provides a clear, Tempered Safety Glass Lens that should only be used with open MR16 Lamps; not with MR16 Lamps that contain an integral Glass Lens
- If use of MR16 with Front Glass is required, remove the factory provided Safety Lens; Lens should also be removed when using MR16 LED Lamps
- Consult factory for LED Lamp compatibility



**CTR1601-P-WHT**  
Adjustable White Baffle  
White Trim

### CTR1601 Series

*Adjustable Baffle*  
3-1/2" I.D., 5-1/2" O.D.

Deep Baffle traps stray light and conceals Lamp. May be used as Downlight or Adjustable Accent Light with 60° swing adjustment.

Trim can hold up to two (2) lenses with included Stepped Lens Holder: 45mm Lens on lower level 50mm Lens onto higher level.

A 75W Lamp may be used in LVR1675 housings. To convert trims, order the **1624 SOCKET-75W** Socket Replacement.

Standard Trims: 5-1/2" OD

- CTR1601-B** - Black Baffle, Black Trim
- CTR1601-P-WHT** - White Baffle, White Trim

Cast Aluminum Trim: 5-1/8" OD

- CTR1601-PA-WHT** - White Baffle



**CTR1602-P-CLR**  
Adjustable Multiplier:  
Clear Reflector, White Trim

### CTR1602 Series


*Adjustable Multiplier*  
3-1/2" I.D., 5-1/2" O.D.

Highly polished Specular Reflector maximizes light intensity while concealing the light source. May be used as Downlight or Adjustable Accent Light with 35° swing adjustment.

Trim can hold up to two (2) lenses with included Stepped Lens Holder: 45mm Lens on lower level 50mm Lens onto higher level.

A 75W Lamp may be used in LVR1675 housings. To convert trims, order the **1624 SOCKET-75W** Socket Replacement.

- CTR1602-B-BLK** - Black Refl., Black Trim
- CTR1602-P-BLK** - Black Refl., White Trim
- CTR1602-P-CLR** - Clear Refl., White Trim
- CTR1602-P-WHT** - White Refl., White Trim



**CTR1603-P**  
White Slotted Wall Wash

### CTR1603 Series

*Slotted Wall Wash*  
1-5/16" I.D., 5-1/2" O.D.

Slot aperture permits maximum beam area adjustment for wall wash or concealed accent lighting effects. 50° Swing adjustment, 358° rotation. 50mm Lens.

A 75W Lamp may be used in LVR1675 housings. To convert trims, order the **1624 SOCKET-75W** Socket Replacement.

**CTR1603-P** - White Slotted Wall Wash,  
Black Interior



**CTR1614-P-CLR**  
White Angled Wall Wash

### CTR1614 Series

*Angled Wall Wash*  
3-7/16" I.D., 5-1/16" O.D.

Adjustable lampholder; 55-75° aiming angle. 45mm lens.

A 75W Lamp may be used in LVR1675 housings. To convert trims, order the **1624 SOCKET-75W** Socket Replacement.

**CTR1614-P-CLR** - Angled Wall Wash:  
Clear Reflector,  
White Trim

Continued on page 2

DATE

PROJECT

TYPE

## LVR16 SERIES | Trims for 4-Inch Low Voltage Downlights

- A Black finish Retaining Ring is standard on Adjustable Trims. For a White finish Retaining Ring, order part number **1623/24 WHITE**.
- These Adjustable Trims will only accept one (1) Lens:
  - If a FA-16 45MM Louver is required, remove the Safety Lens and use a Front Glass MR16 Lamp.
  - A series of 47mm tempered color or light controlling lenses may be used instead of the clear lens supplied.



**CTR1607-P-WHT**  
Adjustable White Pin Spot  
White Baffle & Trim

**CTR1607 Series**  
*Adjustable Pin Spot*  
2" I.D., 4-3/4" O.D.

Low profile gimbal design for aiming flexibility.  
35° Swing adjustment.

Trim can hold up to two (2) lenses with included  
Stepped Lens Holder: 45mm Lens on lower level  
50mm Lens onto higher level.

A 75W Lamp may be used in LVR1675 housings.  
To convert trims, order the **1624 SOCKET-75W**  
Socket Replacement.



**CTR1606-P**  
White Surface Adjustable

**CTR1606 Series**  
*Surface Adjustable*  
1-3/4" I.D., 4-15/16" O.D.

45° Max. vertical and 359° rotational aiming.  
Die-cast aluminum construction. Front access  
for re-lamping. 50mm lens.

A 75W Lamp may be used in LVR1675 housings.  
To convert trims, order the **1624 SOCKET-75W**  
Socket Replacement.



**CTR1624-NK**  
Nickel Fully Adjustable  
Square in Round

**CTR1624 Series**  
*Fully Adjustable Square in Round*  
5-1/2" O.D.

87° Vertical and 359° rotation adjustment.  
Die-cast aluminum construction. Front access,  
spring latch Lamp Retainer Ring (black finish).  
47mm lens. Depth from ceiling: 2-1/2"

A 75W Lamp may be used in LVR1675 housings.  
To convert trims, order the **1624 SOCKET-75W**  
Socket Replacement.

**CTR1607-P-WHT** - Adjustable Pin Spot,  
White Baffle & Trim

**CTR1606-P** - White Surface Adjustable

**CTR1624-B** - Black  
**CTR1624-NK** - Nickel  
**CTR1624-P** - White