

# CTL610

## Ultimate Universal Line Voltage Track Fixture

### Specifications/Features

#### Fixture

Low profile side swivel design with modular component flexibility, Shade options provide a number of light control and style combinations. Can also be used as a bare lamp holder.

"Sure-Set" swivel for precise aiming.

Molded of durable Lexan™ 940.

Integral ON/OFF switch and track polarity indicator are standard.

#### Lamp

**CTL610:** (1) 150W PAR38, E26 Medium Skirted Base

**CTL610/LA620:** (1) 50W PAR20, E26 Medium Skirted Base

**CTL610/LA630:** (1) 75W PAR30 Short Neck, E26 Medium Skirted Base

**CTL610/LA638:** (1) 60W or 75W PAR 16, (1) 50W PAR20 or (1) 150W PAR38, E26 Medium Skirted Base

**CTL610/LA6838:** (1) 150W PAR38, E26 Medium Skirted Base

#### Warranty

This fixture is covered by ConTech's full one (1) year replacement guarantee after date of purchase.

#### Listing

cULus listed. Suitable for dry locations.

#### Fixture Compatibility

Standard ConTech track fixtures are cCSAus certified as-is for use with ConTech's many track systems, as well as with Juno®<sup>1</sup> Lighting track. By changing the prefix in the part number, ConTech can install inserts which make our fixtures compatible with other manufacturers. Replace "CTL" with "HTL" for Halo®<sup>2</sup> track, and "LTL" for Lightolier®<sup>3</sup> track. For more information, please consult our factory.

#### Ordering Information

Example Order:  -

Fixture	Finish	Lampshade	Black Accessory Clips <sup>4</sup>	Accessories <sup>4</sup>
<input type="text" value="CTL610"/>	<input type="text" value="P"/>	<input type="text" value="LA630-P"/>	<input type="text" value="FA-37A"/>	<input type="text" value="LF30-LS"/>
<b>CTL610</b> <b>HTL610</b> <b>LTL610</b>	<b>B</b> - Black <b>P</b> - White <b>S</b> - Silver	<b>LA620-(B,P,S)<sup>4</sup></b> - PAR20 Shade <b>LA630-(B,P,S)</b> - PAR30 Shade <b>LA6838-(B,P,S)</b> - PAR38 Shade <b>LA638-(B,P,S)</b> - Lamp Collar for PAR16, PAR20 or PAR38 lamps	<b>FA-37A</b> - For use with LA630 Shade <b>FA-37B</b> - For use with LA6838 Shade	<b>LF30-(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV)</b> - 4-11/16" Dia. Tempered Glass Lenses for use with LA630 Shade <b>LA-38-(B,P,S)</b> - Egg-Crate Louver for use with LA630 Shade <b>LF40-(A, B, CL, G, LB, R, RO, Y, 73, LS, SL, UV)</b> - 5-7/16" Dia. Tempered Glass Lenses for use with LA6838 Shade <b>LA-39-(B,P,S)</b> - Egg-Crate Louver for use with LA6838 Shade



DIMENSIONS			
Model	A	B	C
<b>CTL610</b>	2-3/4"	2-1/4"	4-7/8"
<b>CTL610/LA620</b>	4-1/2"	3-1/2"	6-1/2"
<b>CTL610/LA630</b>	4-3/4"	4-3/4"	7"
<b>CTL610/LA638</b>	3-3/4"	2-1/4"	5-3/4"
<b>CTL610/LA6838</b>	6-7/8"	5-7/8"	9"

1. Juno is a registered trademark of Juno Lighting  
2. Halo is a registered trademark of Cooper Lighting  
3. Lightolier is a registered trademark of Philips Lighting  
4. Accessory clips and lenses not available for LA620 Shade

Color/Pattern Legend: **-A** (Amber), **-B** (Blue), **-CL** (Clear), **-G** (Green), **-LB** (Light Blue), **-R** (Red), **-RO** (Rose), **-Y** (Yellow), **-73** (Spread Lens), **-LS** (Linear Spread Lens), **-SL** (Soft Light), **-UV** (Optivex UV Filter)