

NTEK/NHTEK

2-Circuit/2-Neutral 120V and 277V Series Track

Specifications/Features

Track

Ideal for dimming intensive applications.

Independent neutrals guarantee that the two circuits are completely isolated, eliminating cross-circuit interference and enable greater power capacity (2 x 20A) than common neutral track.

Superior dimming capability gives the ability to dim on two independent circuits without harmonics or interference on the neutral conductor.

Oversized conductors for higher operating safety and reduced overload potential.

Secure Bus Bar Insulation secured both conductors and insulation for the life of the product.

Separate mechanical suspension points provide superior weight bearing capacity, ensure electrical contact integrity and reduce the likelihood of arcing.

Polarity ridge takes the guesswork out of connector and track alignment during installation.

Made of architectural grade extruded aluminum. Can be field cut to desired length.

Compatibility



NTEK70

All ConTech track luminaires must have an NTEK adapter installed.

For 120V track, fixture adapter NTEK70 must be ordered separately (NTEK70).



For 277V Track, fixture adapter must be factory installed.

Warranty


Track is covered by ConTech's one (1) year full replacement guarantee after date of purchase.

Listing

cULus listed.



Track Section



Recessed Track Jacket Section

Ordering Information

Example Order: - -

Track Sections

Track Finish

- NTEK44** - 4' (48") Length 120V Track
- NTEK48** - 8' (96") Length 120V Track
- NTEK412** - 12' (144") Length 120V Track
- NHTEK44** - 4' (48") Length 277V Track
- NHTEK48** - 8' (96") Length 277V Track
- NHTEK412** - 12' (144") Length 277V Track

- B** - Black
- P** - White
- S** - Silver

Recessed Track Jacket Sections

Jacket Finish


- NFTP44** - 4' (48") Length;
51-1/2" Actual Length
- NFTP48** - 8' (96") Length;
99-1/2" Actual Length
- NFTP412** - 12' (144") Length;
147-1/2" Actual Length

- B** - Black
- P** - White

NTEK/NHTEK

2-Circuit/2-Neutral Track Installation Accessories

120V and 277V Series





Live End Feeds

NTEK11-(B,P,S) 120V
NHTEK11-(B,P,S) 277V

Live End Feed


NTEK12-(B,P,S) 120V
NHTEK12-(B,P,S) 277V

Live End Feed, Reverse Polarity



Live Middle Feed


NTEK14-(B,P,S) 120V
NHTEK14-(B,P,S) 277V



Linear Coupler

NTEK21-(B,P,S) 120V
NHTEK21-(B,P,S) 277V

Does not add length to track run





Dead Ends

NTEK41-(B,P,S) 120V
NHTEK41-(B,P,S) 277V

Recessed End Cap

NFTP41-U


For safe, flush mounting applications.
Natural galvanized steel.



Feedable L-Connector

NTEK34-(B,P,S) 120V
NHTEK34-(B,P,S) 277V

Adjustable Polarity




Outlet Box Cover

NGES15-(B,P,S)

120V Fixture Adapter

NTEK70-(B,P,S)

Switchable between circuits and on/off.
Consult factory for 277V.



Track Length and Field Cutting Tool

NXTSV12



All-in-one hand tool, bends conductors to manufacturer specifications and includes gauge to verify correct length.



Stem Kits

NSPUS12-(B,P) 12" Stem
NSPUS18-(B,P) 18" Stem
NSPUS24-(B,P) 24" Stem
NSPUS48-(B,P) 48" Stem

Includes stem and canopy.




Feedable T-Connectors

NTEK39-(B,P,S) 120V
NHTEK39-(B,P,S) 277V

Feedable T-Connector, Adj. Right Polarity

NTEK40-(B,P,S) 120V
NHTEK40-(B,P,S) 277V

Feedable T-Connector, Adj. Left Polarity




Feedable X-Connector

NTEK38-(B,P,S) 120V
NHTEK38-(B,P,S) 277V


Adjustable Connector

NTEK24-(B,P,S) 120V
NHTEK24-(B,P,S) 277V



NTEK/NHTEK

2-Circuit/2-Neutral Track Installation Accessories 120V and 277V Series



Ceiling Mount Accessories

NSKB30-(B,P,S) Ceiling Cup

For threaded rod or cable mount (rod/cable not included).

NSKB31 Threaded Rod

1/4" Dia., 6' Length. UNLook Finish.

NSKB32-(B,P,S) Plastic Covering Tube

65' Rolls only. For covering threaded rod.


NSKB34 5' Cable

NSKB34/3M 9' Cable

Custom lengths as special order. UNLook Finish.

NSKB12-(B,P,S) Mounting Clip


For threaded rod or cable mount (rod/cable not included).



Mounting Clips

NSKBX12-(B,P,S) Deep Tile Mounting Clips

NSKBT12-(B,P,S) Mounting Clips for T-Bar Ceilings




Stem Suspension Points

NSP4P-(B,P,S) Universal Suspension Point



Includes bracket and cover, stem not included. Also works with cable and threaded rod suspension.

Track Dimensions and Configurations

NTEK and NHTEK track are polarized and manufactured with indentifying ridges (dotted line on diagrams). Refer to these diagrams to ensure proper connector selection.



*Actual dimensions or field cut to length



KEY:

- 1 - NTEK11 Live End Feed
- 1 - NTEK12 Live End Feed Reverse Polarity
- 2 - NTEK21 Linear Coupler
- 3 - NTEK14 Live Middle Feed
- 4 - NTEK34 Feedable L-Connector Adj. Polarity
- 5a - NTEK39 Feedable T-Connector Adj. Polarity
- 5b - NTEK40 Feedable T-Connector Adj. Left Polarity
- 6 - NTEK38 Feedable X-Connector