

CATALOG NO.

PROJECT

## **CY3 SERIES** | 3-1/2-Inch Round Indoor/Outdoor Cylinders: Dimming Specifications

DATE

TYPE

## DIMMING SPECIFICATIONS

- Incandescent 120VAC Dimmers adjust the light with forward phase control, where the dimmer "chops" the forward part of the AC wave to deliver less or more power to the light source; no neutral wire connection required
- Electronic Low Voltage 120VAC Dimmers adjust the light with reverse phase control, where the dimmer "chops" the back part of the AC wave to deliver less or more power to the light source; neutral wire connection required
- 0-10V DC Low Voltage Dimmers operate using two (2) low voltage dimming wires that are separate from the 120V or 277V AC power. The Dimmer sends
  a variable output voltage to the luminaire based upon the dimming level. 10V Corresponds to undimmed operation, 5V to 50% and so on. Switching on/off
  is controlled with the line voltage power input (120V or 277V AC) to the Dimmer and then dimming operation is controlled with the 0-10V DC low voltage
  wiring connection between the Dimmer and the Driver. The control signal runs on two low voltage control wires (color coded violet and pink/gray).
- Lutron EcoSystem Drivers provide continuous dimming from 1%-100%; for a complete list of compatible dimmers and controls, please visit www.lutron.com

			CY3S/CY3T* Dimming Option 12D1 or MVD2
Manufacturer	Dimmer Series	Model	Light Output
Leviton	IllumaTech	IPI06-1LZ	1%-100%
Leviton	SureSlide	6631-2	1%-100%
Leviton	Vizia	VPE06	9%-100%
Leviton	Trimatron	6683-IW	4%-100%
Leviton	Decora	6161	15%-100%
Leviton	SureSlide	6633-P	0%-100%
Leviton	IllumaTech	IPE04	6%-100%
Leviton	IllumaTech	IP710-DLX	N/A
Lutron	Ariadni	TGCL-153P	4%-100%
Lutron	Ariadni	TG-600P	11%-100%
Lutron	Diva	DVCL-153P	0%-100%
Lutron	Diva	DV600P	0%-100%
Lutron	Diva	DVELV303P	6%-100%
Lutron	Diva	DVTV	N/A
Lutron	Faedra	FAELV500	12%-100%

			CY3S/CY3T* Dimming Option 12D1 or MVD2
Manufacturer	Dimmer Series	Model	Light Output
Lutron	Lumea	LG600P	5%-100%
Lutron	Maestro	MAELV600	11%-100%
Lutron	Nova	NFTV	N/A
Lutron	Nova T	NTFTV	N/A
Lutron	Skylark	S-603PG	4%-96%
Lutron	Skylark	S600P	1%-100%
Lutron	Skylark	SELV300P	7%-100%
Lutron	Skylark	CT103P	9%-100%
Pass & Seymour	Titan	CD4FB-W	N/A
Watt Stopper	Miro Decorator	DCLV1	N/A
Synergy		ISD BC	N/A
Cooper	Devine	DLC03P	1%-100%
Cooper	Skye	SLC03P	0%-100%
Cooper	Decorator	DAL06P	0%-100%

\*277V Phase Dimming is not available

## NOTES

1. Testing was performed with a single fixture connected to dimmer.

2. Testing has been performed on these dimmers, but this does not imply any warranty of compatibility.

3. Dimming performance can be influenced by different loads, as well as variations in dimmer switches within the same model.

4. Dimmer maximum load rating with LED may differ from published traditional source dimmer ratings. Consult manufacturer for maximum dimmer information.

5. Consult factory for additional dimming information.