

RDA6L SERIES | O3 Adjustable Recessed Multiple Dimming Specifications

- Incandescent 120VAC dimmers adjust the light with “forward phase control,” where the dimmer “chops” the forward part of the AC wave to deliver less or more power to the light source. No neutral wire connection required.
- Electronic low voltage 120VAC dimmers adjust the light with “reverse phase control,” where the dimmer “chops” the back part of the AC wave to deliver less or more power to the light source. Neutral wire connection required.
- 0-10V DC low voltage dimmers operate using two low voltage dimming wires that are separate from the 120V or 277V AC power. The dimmer sends a variable output voltage to the fixture based upon the dimming level. 10V corresponds to undimmed operation, 5V to 50% and so on. Switching on/off is controlled with the line voltage power (120V or 277V AC) input to the dimmer and then dimming operation is controlled with the 0-10V DC low voltage wiring connection between the dimmer and the LED driver. The control signal runs on two low voltage control wires (color coded violet and pink/gray).
- Lutron EcoSystem Drivers provide continuous dimming from 1%-100%. For a complete list of compatible dimmers and controls, please visit www.lutron.com

			RDA6* Dimming Option 12D1 or 27D2
Manufacturer	Product	Model	Light Output
Leviton	IllumaTech	IPI06-1LZ	1%-100%
Leviton	SureSlide	6631-2	1%-100%
Leviton	Renoir	AWSMT7	22%-100%
Leviton	Vizia	VPE06	9%-100%
Leviton	Trimatron	6683-IW	6%-100%
Leviton	Decora	6161	15%-100%
Leviton	SureSlide	6633-P	1%-100%
Leviton	IllumaTech	IPE04	6%-100%
Leviton	IllumaTech	IP710-DLX	NA
Cooper	Devine	DLC03P	1%-100%
Cooper	Skye	SLC03P	0%-100%
Cooper	Decorator	DAL06P	0%-100%
Pass & Seymour	Titan	CD4FB-W	NA
Synergy		ISD BC	NA
Watt Stopper	Miro Decorator	DCLV1	NA
Lutron	Ariadni	TGCL153P	1%-100%
Lutron	Ariadni	TG-600P	13%-100%
Lutron	Diva	DVCL153P	1%-100%
Lutron	Diva	DV600P	6%-100%
Lutron	Diva	DVELV303P	6%-100%
Lutron	Diva	DVTV	NA
Lutron	Diva	DVSTWH	8%-100%
Lutron	Faedra	FAELV500	12%-100%
Lutron	Lumea	LG600P	8%-100%
Lutron	Maestro	MAELV600	16%-100%
Lutron	Nova	NFTV	NA
Lutron	Nova T	NTFTV	NA
Lutron	Skylark	S-603PG	5%-96%
Lutron	Skylark	S600P	5%-100%
Lutron	Skylark	SELV300P	10%-100%
Lutron	Skylark	CT103P	9%-100%

*277V TRIAC Dimming is not available

NOTES

1. Testing was performed with a single luminaire connected to Dimmer.
2. Testing has been performed on these Dimmers, but this does not imply any warranty of compatibility.
3. Dimming performance can be influenced by different Loads, as well as variations in Dimmer Switches within the same Model.
4. Dimmer Maximum Load Rating with LED may differ from published Traditional Source Dimmer Ratings. Consult manufacturer for maximum Dimmer information.
5. Consult factory for additional dimming information.