

Specflex
Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot


24V Architectural Flex Strip, Static White, 73 LEDs per foot

This series offers a range of outputs, all with excellent color rendering and consistency. Designed for reliable performance and ease of use. Ideal for cove, slot, undercabinet, millwork details, architectural reveals, and endless accent lighting applications.



FEATURES

- High Density: 73 LEDs per foot
- Three (3) Wattage/Lumen options
- 95+ CRI and <2 SDCM ensures excellent color rendering and consistency
- Full Reels or Factory Cut into Custom Lengths
- Low power consumption with consistent, stable performance
- Wide range of Dimming and Non-dimming LED Drivers, Connectors, Mounting Channels, and Lenses
- Declare Listed
- Complete System is cCSAus Listed to UL and CSA Standards



SERIES	AFSS73-3	AFSS73-5	AFSS73-7
WATTAGE	3W/Ft	5W/Ft	7W/Ft
LUMEN OUTPUT ¹	370Lm/Ft	593Lm/Ft	762Lm/Ft
EFFICACY ¹	123Lm/W	119Lm/W	117Lm/W
MAX RUN LENGTH	26.2Ft	21.3Ft	16.4Ft
LED DENSITY	73 LEDs/Ft		
CUT INCREMENT	1.31-Inches (33mm), Field Cuttable		
STRIP LIGHT WIDTH	0.39-Inches (10mm)		
MOUNTING	3M™ 300LSE Double Sided Tape / Channels & Clips		
COLOR TEMPERATURE	2700K / 3000K / 3500K / 4000K / Consult factory for additional CCT options		
CRI	95+, R9 >84		
COLOR CONSISTENCY	<2 SDCM (Standard Deviation Color Matching)		
OPERATING VOLTAGE	24V DC		
DIMMING	Forward / Reverse Phase and 0-10V		
OPERATING TEMP.	-25° to 40°C (-13° to 104°F)		
LIFE RATING	50,000 Hours @ 70% Lumen Maintenance		
LISTINGS	cCSAus Listed to UL Standards and CSA Standards Suitable for Dry Locations, IP20 Rated. For Wet Location rated options, see AFSS73 Wet Location Series Closet Rated up to and including 5W/Ft Series (AFSS73-5) when used with Channel, Endcaps and Lens Declare Listed RoHS Compliant For use with Class 2 LED Drivers only		
WARRANTY	Five (5) year replacement after date of purchase when installed within a ConTech Mounting Channel Three (3) year replacement after date of purchase when installed without a ConTech Mounting Channel		

1. Approximate lumen output based on 3000K performance; see photometric test results for additional information

Specflex
Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

ORDERING INFORMATION

FULL REELS

- Full Reels are available in Max Run Length for each available Wattage
- Each Reel has a 72-inch Plenum Rated Cable Power Lead soldered to the start of the length
- Additional Plenum Rated Cable available (ordered separately), see Page 9 for details
- Reels can be cut in the field to desired length at the indicated cut points; excess Strip Light can be configured for additional installations

Example Order: AFSS73-330K-R

Series	Wattage	CCT ² /CRI	Illuminated Length
AFSS73 Static White: 73LEDs/Ft	3 3W/Ft	95+ CRI	R Full Reel with 72-inch Power lead 3W/Ft: 26.2 Ft Reel 5W/Ft: 21.3 Ft Reel 7W/Ft: 16.4 Ft Reel
	5 5W/Ft	27K 2700K	
	7¹ 7W/Ft	30K 3000K	
		35K 3500K	
		40K 4000K	


CUSTOM LENGTHS

- Custom Lengths cannot exceed the Maximum Run Length for the specified Wattage; see Max Run Length table on Page 14
- Allow additional lead time for Custom Lengths
- Custom Lengths are made-to-order and are not returnable; approved Submittal Sheets are required before processing the order

Example Order: AFSS73-330K-S-NT-C188

Series	Wattage	CCT ² /CRI	Start Termination	End Termination	Custom Length
AFSS73 Static White: 73LEDs/Ft	3 3W/Ft	27K 2700K	F Female Barrel Connector M Male Barrel Connector S³ 72-inch Soldered Lead Wires SXXX³ Custom Length Soldered Lead Wires	NT No Termination F Female Barrel Connector M Male Barrel Connector S³ 72-inch Soldered Lead Wires SXXX³ Custom Length Soldered Lead Wires	CXXX Custom Length Desired length is specified in inches i.e. if the desired length is 15 Ft.-8-Inches or 188-inches total, enter C188 AFSS73 Series has a cut increment of 1.31-inches, illuminated length will be rounded down to nearest cut increment
	5 5W/Ft	30K 3000K			
	7¹ 7W/Ft	35K 3500K			
		40K 4000K			

1. 7W Series not approved for use in closets
2. Consult factory for additional CCT options; additional lead time for special request CCTs
3. All Lead Wires come sheathed in a Plenum Rated Cable rated to 90°C minimum; specify Custom Length Lead Wires in inches; max length: 120-inches



Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V MOUNTING CHANNELS AND ACCESSORIES

ALUMINUM MOUNTING CHANNEL

- Provides excellent heat sinking and protection to the LEDs while ensuring a clean, straight run
- Anodized Satin Aluminum Channel
- All Channels and Accessories are Declare Listed

CHANNEL MOUNTING CLIPS


- Stainless Steel and Adjustable Mounting Clip is ABS Plastic
- 24-Inches between clips recommended for most applications

CHANNEL ENDCAPS


- Creates a clean finish to the Mounting Channel
- ABS Grey Plastic
- Endcaps are ordered individually; one (1) solid Endcap and one (1) open Endcap (with Slot) is recommended
- Use Endcaps with Slots for Power Feed

Channel, Lens, Endcaps, and Mounting Clips are ordered separately


BEAM FOCUSING MOUNTING CHANNEL




Beam Focusing Mounting Channel




Beam Focusing Optic
(Shown in Channel)




Beam Focusing Channel Endcap



Beam Focusing Channel Endcap with Hole




Beam Focusing Channel Mounting Clips



Beam Focusing Channel Adjustable Mounting Clips

SELECT 1 OF 5 CONFIGURATIONS: (BEAM SPREADS NOT FIELD CHANGEABLE)



Insert

Included with channel



Grazer
19°




Narrow
36°



Medium
45°



Flood
55°



Wide Flood
67°

Channel and Optic
AFEX1112BEAMS78-S 78-Inch Beam Focusing Mounting Channel with Insert AFL1112BEAMS78-FR 78-Inch Beam Focusing Optic, Frosted; No Pixelation with Optic

Endcaps
AFEX1112BEAMS-EC Beam Focusing Channel Solid Endcap, Grey AFEX1112BEAMS-ECH Beam Focusing Channel Endcap with Hole, Grey

Mounting Clips
AFEX1112BEAMS-MC4 Four (4) Mounting Clips, Stainless Steel AFEX1112BEAMS-AMC6 Six (6) Adjustable Mounting Clips, Grey

For Photometrics, see page 13

Channel Series not compatible with Screw-Tight Connectors

Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V MOUNTING CHANNELS AND ACCESSORIES


NARROW SURFACE MOUNTING CHANNEL



Channel and Lens	Endcaps
AFEX1012S72-S 6 Ft. Narrow Surface Mounting Channel, Aluminum AFL10S72-FR 6 Ft. Narrow Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens	AFEX1012S-EC Narrow Surface Channel Solid Endcap, Grey AFEX1012S-ECS Narrow Surface Channel Endcap with Slot, Grey


Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor
Channel Series not compatible with Screw-Tight Connectors

SHALLOW SURFACE MOUNTING CHANNEL



Channel and Lens	Endcaps	Mounting Clips
AFEX1209S72-S 6 Ft. Shallow Surface Mounting Channel, Aluminum AFL1272-FR 6 Ft. Shallow Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens	AFEX1209S-EC Shallow Surface Channel Solid Endcap, Grey AFEX1209S-ECS Shallow Surface Channel Endcap with Slot, Grey	AFEX12S-MC4 Four (4) Mounting Clips, Stainless Steel

DEEP SURFACE MOUNTING CHANNEL



Channel and Lens	Endcaps	Mounting Clips
AFEX1215S72-S 6 Ft. Deep Surface Mounting Channel, Aluminum AFL1272-FR 6 Ft. Deep Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens	AFEX1215S-EC Deep Surface Channel Solid Endcap, Grey AFEX1215S-ECS Deep Surface Channel Endcap with Slot, Grey	AFEX12S-MC4 Four (4) Mounting Clips, Stainless Steel

Specflex


Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V MOUNTING CHANNELS AND ACCESSORIES


WIDE SURFACE MOUNTING CHANNEL



Channel and Lens	
AFEX1508S72-S	6 Ft. Wide Surface Mounting Channel, Aluminum
AFL1572-FR	6 Ft. Wide Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor

EXTRA WIDE SURFACE MOUNTING CHANNEL




Channel and Lens	
AFEX2011S72-S	6 Ft. Extra Wide Surface Mounting Channel, Aluminum
AFL2072-FR	6 Ft. Extra Wide Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Endcaps	
AFEX2011S-EC	Extra Wide Surface Channel Solid Endcap, Grey
AFEX2011S-ECS	Extra Wide Surface Channel Endcap with Slot, Grey

Mounting Clips	
AFEX2011S-MC4	Four (4) Mounting Clips, Stainless Steel

45° ANGLED MOUNTING CHANNEL



Channel and Lens	
AFEX1016A72-S	6 Ft. 45° Angled Mounting Channel, Aluminum
AFL10A72-FR	6 Ft. 45° Angled Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Endcaps	
AFEX1016A-EC	45° Angled Channel Solid Endcap, Grey
AFEX1016A-ECS	45° Angled Channel Endcap with Slot, Grey

Mounting Clips	
AFEX1016A-MC4	Four (4) Mounting Clips, Stainless Steel

Channel Series not compatible with Screw-Tight Connectors

Specflex


Architectural Strip Lighting

AFSS73 Dry Location Series


24V Static White, High Density 73 LEDs per foot

24V MOUNTING CHANNELS AND ACCESSORIES


45° ANGLED WIDE MOUNTING CHANNEL




45° Angled Wide Mounting Channel




Frosted Diffusion Lens
(Shown in Channel)



45° Angled Wide Channel Endcap




45° Angled Wide Channel Endcap with Slot




45° Angled Wide Channel Mounting Clips

Channel and Lens AFEX1318A72-S 6 Ft. 45° Angled Wide Mounting Channel, Aluminum AFL1372-FR 6 Ft. 45° Angled Wide Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens	Endcaps AFEX1318A-EC 45° Angled Wide Channel Solid Endcap, Grey AFEX1318A-ECS 45° Angled Wide Channel Endcap with Slot, Grey	Mounting Clips AFEX1318A-MC4 Four (4) Mounting Clips, Stainless Steel
---	---	---


45° ANGLED EXTRA WIDE MOUNTING CHANNEL




45° Angled Extra Wide Mounting Channel



Frosted Diffusion Lens
(Shown in Channel)



45° Angled Extra Wide Channel Endcap



45° Angled Extra Wide Channel Endcap with Slot

Channel and Lens AFEX2030A72-S 6 Ft. 45° Angled Extra Wide Mounting Channel, Aluminum AFL20A72-FR 6 Ft. 45° Angled Extra Wide Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens	Endcaps AFEX2030A-EC 45° Angled Extra Wide Channel Solid Endcap, Grey AFEX2030A-ECS 45° Angled Extra Wide Channel Endcap with Slot, Grey
--	---

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor


Specflex
Architectural Strip Lighting

AFSS73 Dry Location Series


24V Static White, High Density 73 LEDs per foot

24V MOUNTING CHANNELS AND ACCESSORIES


SHALLOW RECESSED MOUNTING CHANNEL




Shallow Recessed Mounting Channel



Frosted Diffusion Lens
(Shown in Channel)



Shallow Recessed Channel Endcap



Shallow Recessed Channel Endcap with Slot

Channel and Lens


- AFEX1209R72-S** 6 Ft. Shallow Recessed Mounting Channel, Aluminum
AFL1272-FR 6 Ft. Shallow Recessed Channel Diffusion Lens, Frosted;
 No Pixelation with Diffusion Lens

Endcaps


- AFEX1209R-EC** Shallow Recessed Channel Solid Endcap, Grey
AFEX1209R-ECS Shallow Recessed Channel Endcap with Slot, Grey

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor


DEEP RECESSED MOUNTING CHANNEL




Deep Recessed Mounting Channel




Frosted Diffusion Lens
(Shown in Channel)



Deep Recessed Channel Endcap



Deep Recessed Channel Endcap with Slot



Deep Recessed Channel Mounting Clips

Channel and Lens

- AFEX1215R72-S** 6 Ft. Deep Recessed Mounting Channel, Aluminum
AFL1272-FR 6 Ft. Deep Recessed Channel Diffusion Lens, Frosted;
 No Pixelation with Diffusion Lens


Endcaps

- AFEX1215R-EC** Deep Recessed Channel Solid Endcap, Grey
AFEX1215R-ECS Deep Recessed Channel Endcap with Slot, Grey


Mounting Clips

- AFEX1215R-MC4** Four (4) Mounting Clips, Stainless Steel


EXTRA WIDE RECESSED MOUNTING CHANNEL




Extra Wide Recessed Mounting Channel



Frosted Diffusion Lens
(Shown in Channel)



Extra Wide Recessed Channel Endcap



Extra Wide Recessed Channel Endcap with Slot

Channel and Lens

- AFEX2011R72-S** 6 Ft. Extra Wide Recessed Mounting Channel, Aluminum
AFL2072-FR 6 Ft. Extra Wide Recessed Channel Diffusion Lens, Frosted;
 No Pixelation with Diffusion Lens

Endcaps

- AFEX2011R-EC** Extra Wide Recessed Channel Solid Endcap, Grey
AFEX2011R-ECS Extra Wide Recessed Channel Endcap with Slot, Grey

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor

Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V CONNECTORS

TLCC Series

Barrel Connectors

- 6-Inch long Male and Female Connector
- Includes Wire Pigtail
- Hardwire to LED Driver for easy plug in connection

Model Number
TLCCM Male barrel connector
TLCCF Female barrel connector



TLCS Series

Plug-and-Play Power Splitter

- Approximately 2 feet long
- 2-Way: one (1) Male and two (2) Female Connectors
- 3-Way: one (1) Male and three (3) Female Connectors

Model Number
TLCS2 Plug-and-play 2-way power splitter
TLCS3 Plug-and-play 3-way power splitter



TLCEXT Series

Plug-and-Play Power Extension

- Select from 24-, 36-, 48- and 96-inch lengths
- Male Plug Connector on one end, Female Plug Connector on other

Model Number
TLCEXT24 24 Inch power extension
TLCEXT36 36 Inch power extension
TLCEXT48 48 Inch power extension
TLCEXT96 96 Inch power extension



24V SCREW-TIGHT CONNECTORS

Screw-Tight Connectors not compatible with AFEX1012S, AFEX1016A, and AFEX1112BEAMS Mounting Channel Series

AFCTITEUDL12-W

Universal Screw-Tight Power Lead Connector

- Includes 12-inch Plenum Rated Cable Power Lead, 3M™ VHB Adhesive Backing, and 1.3mm Hex Wrench
- Length may be modified in field, see Installation Instructions for details
- Use to connect Power Lead to Strip Light
- 17/32"L x 15/32"W x 9/32"H
- Max Current: 10A

Model Number
AFCTITEUDL12-W Universal screw-tight connector with white CMP lead cable



AFCTITEUDJ12-W

Universal Screw-Tight Jumper Connector

- Includes 12-inch Plenum Rated Cable Power Lead, 3M™ VHB Adhesive Backing, and 1.3mm Hex Wrench
- Length may be modified in field, see Installation Instructions for details
- Use to connect two (2) sections of Strip Light
- 17/32"L x 15/32"W x 9/32"H
- Max Current: 10A

Model Number
AFCTITEUDJ12-W Universal screw-tight connector with white CMP jumper cable



AFCTITEUDC

Universal Screw-Tight In-line Connector

- Use to connect two (2) sections of Strip Light in-line
- Includes 3M™VHB Adhesive Backing and 1.3mm Hex Wrench
- 13/32"L x 15/32"W x 9/32"H
- Max Current: 10A

Model Number
AFCTITEUDC Universal screw-tight in-line connector



AFCTITEUDX

Universal Screw-Tight Corner Connector

- Use to connect two (2) sections of Strip Light at a right angle
- Includes 3M™VHB Adhesive Backing and 1.3mm Hex Wrench
- 11/16"L x 15/32"W x 9/32"H
- Max Current: 10A

Model Number
AFCTITEUDX Universal screw-tight corner connector



Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V ACCESSORIES

Plenum Rated Cable

Two Conductor Plenum Rated Cable

Model Number			
CMP-2C-10	10Ft	CMP-2C-30	30Ft
CMP-2C-15	15Ft	CMP-2C-50	50Ft
CMP-2C-20	20Ft	CMP-2C-100	100Ft



24V CONTROLLERS

TLPRTW

4-Channel Power Repeater

- Enables synchronized control of multiple runs from one controller
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPRTW	4-Channel Power Repeater (5-5/16" L x 1-3/4" W x 1-1/8" D)



TLPINT

DMX 512 CV Decoder

- Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others)
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPINT	DMX 512 CV Decoder (6-3/16" L x 3-1/8" W x 1-5/8" D)



TLPRGBRF

Dimming Controller with RF Remote Control

- Pre-programmed functions include: Color Strobe, 3- Channel Color Change and Gradual Brightness Change. Includes two (2) programmable presets
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPRGBRF	Dimming Controller w/ RF Remote Control (8-3/8" L x 1-5/8" W x 1-3/16" D)



Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

24V HARDWIRE LED DRIVERS

TLP24VHW Series

Hardwire Constant Voltage Driver

- 120VAC Input / 24VDC Output
- Includes stripped and tinned wire pigtails on the input and output sides
- 1 Foot Wire Leads
- Class 2 Recognized
- MUST BE MAINTAINED WITHIN AN ENCLOSURE THAT MEETS LOCAL BUILDING CODES AND NEC (SUPPLIED BY OTHERS)

Model Number
TLP24VHW20 20W (5-3/4" L x 1-1/2" W x 1-1/4" H)
TLP24VHW60 60W (6-1/3" L x 1-3/4" W x 1-1/4" H)
TLP24VHW96 96W (6-1/8" L x 2-3/8" W x 1-1/2" H)



L3D0 Series

Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade to Black™

- 120-277VAC Input / 24VDC Output
- Enclosed Class 2 Listed Constant Voltage Driver
- 96W Max

Model Number
L3D0-96W24V-U 96W, 24V 120-277VAC (5.5" W x 2" H x 10.5" L)



TLP24VHW*MVD-ENC Series

Hardwire Class 2 Constant Voltage Enclosed Driver

- 120-277VAC Input / 24VDC Output
- Class 2 Listed Constant Voltage UL Listed Enclosed LED Driver
- Forward/Reverse Phase and 0-10V Dimming
- 0-10V Dimming delivers smooth flicker free linear dimming down to 1% with most LEDs and a wide variety of compatible dimmers
- No minimum load requirement. Over voltage, current, temperature, and short-circuit protection.

Model Number
TLP24VHW60MVD-ENC 60W, Forward/Reverse Phase and 0-10V Dimming Driver (8" L x 3-3/8" W x 1-1/4" D)
TLP24VHW100MVD-ENC 96W, Forward/Reverse Phase and 0-10V Dimming Driver (8-1/4" L x 4-1/8" W x 1-1/2" D)



TLP24VHW*MV-ENC & TLP24VHW*MVD2-ENC Series

Hardwire Class 2 Constant Voltage Enclosed Driver

- 120-277VAC Input / 24VDC Output
- Class 2 Listed Constant Voltage UL Listed Enclosed LED Driver with built-in junction boxes; Wet Location Rated
- 0-10V Dimming and Non-dimming Models
- 0-10V Dimming Driver delivers smooth flicker free linear dimming down to 1% with most LEDs and a wide variety of compatible dimmers
- No minimum load requirement. Auto-reset protection for short circuit and over-temperature. Over load protection in CC mode.
- 12-1/8" L x 2-3/8" W x 1-3/8" D

Model Number
TLP24VHW60MV-ENC 60W, Non-dimming Driver
TLP24VHW96MV-ENC 96W, Non-dimming Driver
TLP24VHW60MVD2-ENC 60W, 0-10V Dimming Driver
TLP24VHW96MVD2-ENC 96W, 0-10V Dimming Driver



24V PLUG-IN POWER SUPPLIES

TLP24VP Series

Plug-and-Play Power Supply

- 120VAC Input / 24VDC Output
- Includes AC Wall Plug and Female Power Output Barrel Plug for easy installation
- Class 2 Listed

Model Number
TLP24VP36 36W (4-1/4" L x 2" W x 1-3/8" H)
TLP24VP60 60W (4-1/2" L x 2" W x 1-3/8" H)
TLP24VP96 96W (6-1/8" L x 2-3/8" W x 1-1/2" H)



Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

PRODUCT SPECIFICATIONS

CONSTRUCTION

- High Density Flex Strip: 73 LEDs per foot
- 3-Ounce Copper Construction provides excellent heat dissipation and reduced voltage drop
- Full Reels have 72-inch Soldered Lead sheathed in a Plenum Rated Cable rated to 90°C min.

LEDs

- **Color Temperature:**
2700K, 3000K, 3500K, 4000K
Consult factory for additional CCT options
- **CRI:**
95+, R9 >84
- **Color Consistency:**
<2 SDCM

ELECTRICAL

- **Input Voltage:**
24VDC
- **Average Power Consumption/Wattage:**
3W, 5W, 7W per Foot
- **Dimming:**
Forward / Reverse Phase and 0-10V Dimming
- **Ambient Operating Temp:**
-25° to 40°C (-13° to 104°F)
- System designed and rated for 50,000 hours at 70% lumen maintenance
- Drivers and Controllers ordered separately

INSTALLATION

- Includes 3M™ 300LSE Adhesive Backing for strong adhesion to channels and most smooth surfaces
- Wide selection of Aluminum Mounting Channels are available with or without a Lens, Lens sold separately
- Mounting Channels simplify installation and provide a uniform surface for strip adhesion and thermal management
- Channel Endcaps are available to create a finished appearance to the run; open or closed Endcaps are sold separately
- Mounting Clips available in packs of four (4); includes screws and dry-wall anchors for surface mounting, sold separately
- All Mounting Channels are field cuttable

OPTICS

- Create five (5) Beam Distributions (19 degrees to 67 degrees) using the Beam Focusing Optic (AFL1112BEAMS Series) and Channel with Insert (AFEX1112BEAMS Series)
- Optic and Mounting Channel (includes Insert) ordered separately
- Adjustable Mounting Clips available in packs of six (6); includes screws and dry-wall anchors for surface mounting, sold separately

CERTIFICATIONS

- cCSAus Listed to UL and CSA Standards
- IP20 Rated, suitable for Dry Locations
- Wet Location options available; see AFSS73 Series Wet Location Specification Sheet
- Declare Listed
- RoHS Compliant
- Closet Rated when used with Channel, Endcaps and Lens; 7W Series is not Rated for Closet use

WARRANTY

- Covered by ConTech's full replacement guarantee after date of purchase:
 - Five (5) year replacement after date of purchase when installed within Mounting Channel
 - Three (3) year replacement after date of purchase when installed without Mounting Channel

Declare.

SpecFlex Architectural Striplight ConTech Lighting

Final Assembly: Northbrook, Illinois, USA
Life Expectancy: 5 Year(s)
End of Life Options: Recyclable (35%), Landfill (65%)

Ingredients:

Aluminum; Copper; Carbonic acid, polymer with 4,4'-(1-methylethylidene)bis[phenol]; Polyvinyl chloride; Vinyl fluoride-Vinylidene fluoride-Chlorotrifluoroethylene copolymer; RTV silicone rubber; Ethylene glycol monomethyl ether; Tin, Organic; Plastiquinone; 1,3-Isobenzofurandione, polymer with 2,5-furandione and 2,2'-oxybis[ethanol]; Gold; Titanium dioxide; Silver; Diethylene Glycol

Living Building Challenge Criteria:

I-13 Red List:

- ☐ LBC Red List Free % Disclosed: 100% at 100ppm
☐ LBC Red List Approved VOC Content: Not Applicable
☒ Declared

I-10 Interior Performance: Not Applicable

I-14 Responsible Sourcing: Not Applicable

CNT-0004
 EXP. 01 JUN 2025
 Original Issue Date: 2024

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY
 INTERNATIONAL LIVING FUTURE INSTITUTE™ living-future.org/declare

Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

PHOTOMETRICS



AFSS73-730K: 24V Dry Location SpecFlex Strip Light

7W/Ft, 73LEDs/Ft, 1-Foot Strip, 3082K, 98 CRI

Fixture Delivered Lumens: 762.3
 Total Watts@24: 6.48
 Lumens Per Watt: 117.3
 Center Beam Candle Power: 262
 Beam Distribution: 115°
 Spacing Criterion: 1.28

LM-63 Test No. G23111703
 LM-79 Test No. S23111703

Intensity Distribution		
DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	65.4	6.3
4 FT	16.4	12.6
6 FT	7.3	18.9
8 FT	4.1	25.2
10 FT	2.6	31.5
12 FT	1.8	37.8



1. Colors Present within the Light Source

CCT MULTIPLIERS			
2700K	3000K	3500K	4000K
0.98	N/A	1.02	1.05





OUTPUT MULTIPLIERS		
3W/Ft Series	5W/Ft Series	7W/Ft Series
0.43	0.81	1.00

AFSS73-730K TM-30 DATA

ANSI/IES TM-30-18 Color Rendition Report Test No. S23111703

Colors are for visual orientation purposes only

R _f	96
R _g	102
CCT (K)	3082K
D _{uv}	0.0004
u'	0.2476
v'	0.5203



HUE BIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
HUE SHIFT	-1%	0%	2%	1%	2%	1%	-1%	-1%	-1%	0%	3%	0%	-2%	-3%	-3%	-6%
R _f VALUE	97	98	97	97	97	96	97	97	98	98	95	94	96	94	95	92

Specflex
Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

PHOTOMETRICS

AFSS73-730K + AFEX1112BEAMS + AFL1112BEAMS: 24V Dry Location SpecFlex Strip Light

7W/Ft, 73LEDs/Ft, 1-Foot Strip, 3082K, 98 CRI

Using the Beam Focusing Mounting Channel and Frosted Diffusion Optic combined with the included Channel Insert to achieve tested Beam Spread

Grazer

LM-63 Test No. G22103101




No Insert

Fixture Delivered Lumens: 370.3
Total Watts@24V: 6.3
Lumens Per Watt: 58.8
Center Beam Candle Power: 499
Beam Distribution: 19°
Spacing Criterion: 0.33

Intensity Distribution

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	124.7	0.7
4 FT	31.2	1.3
6 FT	13.9	2.0
8 FT	7.8	2.6
10 FT	5.0	3.3
12 FT	3.5	4.0

Candela Curve



Narrow

LM-63 Test No. G22103102




Fixture Delivered Lumens: 539.2
Total Watts@24V: 7.3
Lumens Per Watt: 73.9
Center Beam Candle Power: 497
Beam Distribution: 36°
Spacing Criterion: 0.62

Intensity Distribution

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	124.2	1.3
4 FT	31.1	2.6
6 FT	13.8	3.9
8 FT	7.8	5.2
10 FT	5.0	6.5
12 FT	3.5	7.9

Candela Curve



Medium

LM-63 Test No. G22103103




Fixture Delivered Lumens: 616.3
Total Watts@24V: 7.5
Lumens Per Watt: 82.2
Center Beam Candle Power: 520
Beam Distribution: 45°
Spacing Criterion: 0.72

Intensity Distribution

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	130.0	1.7
4 FT	32.5	3.3
6 FT	14.4	5.0
8 FT	8.1	6.7
10 FT	5.2	8.3
12 FT	3.6	10.0

Candela Curve



Flood

LM-63 Test No. G22103104




Fixture Delivered Lumens: 595.1
Total Watts@24V: 7.1
Lumens Per Watt: 83.8
Center Beam Candle Power: 428
Beam Distribution: 55°
Spacing Criterion: 0.89

Intensity Distribution

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	107.0	2.1
4 FT	26.8	4.1
6 FT	11.9	6.2
8 FT	6.7	8.3
10 FT	4.3	10.3
12 FT	3.0	12.4

Candela Curve



Wide Flood

LM-63 Test No. G22103105




Fixture Delivered Lumens: 654.7
Total Watts@24V: 7.1
Lumens Per Watt: 92.2
Center Beam Candle Power: 413
Beam Distribution: 67°
Spacing Criterion: 1.03

Intensity Distribution

DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	103.3	2.7
4 FT	25.8	5.3
6 FT	11.5	7.9
8 FT	6.5	10.6
10 FT	4.1	13.2
12 FT	2.9	15.9

Candela Curve



CCT MULTIPLIERS			
2700K	3000K	3500K	4000K
0.98	N/A	1.02	1.05

OUTPUT MULTIPLIERS		
3W/Ft Series	5W/Ft Series	7W/Ft Series
0.43	0.81	1.00

Specflex

Architectural Strip Lighting

AFSS73 Dry Location Series

24V Static White, High Density 73 LEDs per foot

DIMMING SPECIFICATIONS

LED Drivers have been tested with the following Dimmer Models:

TRIAC (LEADING EDGE) DIMMING

Manufacturer	Product	Model
Leviton	SureSlide	6672, 6674, 6674N, 66DF
	Decora Smart	D26HD, D2MSD, DN6HD
	Decora Digital	DDL06-1, DDM06, DDL06-1, DDMX1
	Decora Slide	DSL06, DSM10
	Illuminatech	IPL06
	Trimatron Rotary	RDL06, RNL06
	Toggle Slide	TSL06, TSM10
Lutron	Caseta	PD-6WCL
	Diva	DVCL-153P
	Lumea	LECL-153P
	Maestro	MACL-153M
	Skylark	SCL-153P
	Toggler	TGCL-153P

ELV (TRAILING EDGE) DIMMING

Manufacturer	Product	Model
Leviton	Decora Digital	DDE06
Lutron	Diva	DVELV-300P-WH
	Skylark	SELV-300P-WH

0-10V DIMMING

Manufacturer	Product	Model
Leviton	Illuminatech	IP710-DLX, IP710-LFZ
Lutron	Diva	DVSCSTV, DVSCTV, DVSTV, DVTV, DVTV-WH

- Testing has been performed on these Dimmers, but this does not imply any warranty of compatibility
- Dimming performance can be influenced by different Loads, as well as variations in Dimmer Switches within the same Model
- Dimmer Maximum Load Rating with LED may differ from published Traditional Source Dimmer Ratings; consult manufacturer for maximum dimmer information
- Consult factory for additional dimming information

MAX RUN LENGTH

INPUT = 24VDC

LED Driver	AFSS73-3	AFSS73-5	AFSS73-7
Wattage	Max Run Length		
20W	6 FT	3 FT	2 FT
36W	10 FT	6 FT	4 FT
60W	17 FT	11 FT	8 FT
96W	26 FT	21 FT	16 FT

- Max Run refers to the total single run of Strip Light that can go on a Driver
- Max Run Lengths are calculated with 24V DC at the start of the Strip Light run. Voltage drop may occur if not using proper wire gauge. Refer to the Voltage Drop and Wire Length Distance chart.
- Max Run lengths above are calculated with no more than 30% light loss from the start of the Strip Light run to the end of the Strip Light run for optimal light consistency. If run lengths are extended beyond the recommended lengths noted above, there will be inconsistent light output and voltage drop.
- Overall distance of Strip Light under load (lit length). If exceeded, damage to the Driver and Strip Light may result.

VOLTAGE DROP AND WIRE LENGTH DISTANCE

3% VOLTAGE DROP

Wire Gauge	20W	30W	36W	60W	96W
22 AWG	27 FT	18 FT	15 FT	9 FT	5 FT
20 AWG	43 FT	28 FT	24 FT	14 FT	9 FT
18 AWG	68 FT	45 FT	38 FT	23 FT	14 FT
16 AWG	109 FT	72 FT	60 FT	36 FT	23 FT
14 AWG	174 FT	115 FT	95 FT	57 FT	36 FT
12 AWG	272 FT	181 FT	151 FT	90 FT	57 FT
10 AWG	432 FT	288 FT	240 FT	144 FT	90 FT

The Voltage Drop/Wire Length Distance Chart provides general guidelines for determining wire gauge based on total load and distance from the Driver to the beginning of the Strip Light run.