

Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series


24V Static White, Continuous COB

IP67 Wet Location Rated 24V Architectural Flex Strip, Static White, Continuous COB

This series provides dot-free illumination with excellent color rendering and consistency. Designed for reliable performance in wet location environments. Ideal for indoor and outdoor wet location applications including handrail and step lighting, building, display, and landscape accent lighting.

FEATURES

- IP67 Wet Location Rated
- Continuous COB
- One (1) Wattage/Lumen options
- 90+ CRI and <5 SDCM ensures excellent color rendering and consistency
- Full Reels or Factory Cut into Custom Lengths
- Low power consumption with consistent, stable performance
- Wide range of Dimming and Non-dimming LED Drivers, Connectors, Mounting Channels, and Lenses
- Declare Listed
- Complete System is cCSAus Listed to UL and CSA Standards

cCSAus  
ListedSuitable for  
Wet LocationsDeclare<sup>SM</sup>  
ListedRoHS  
CompliantIP67  
Rated

90+ CRI

Phase/0-10V  
Dimming5  
STEP  
Color  
Consistency

SERIES	AFSSCN-5
WATTAGE	4.6W/Ft
LUMEN OUTPUT <sup>1</sup>	390Lm/Ft
EFFICACY <sup>1</sup>	78Lm/W
MAX RUN LENGTH	16.4Ft
LED DENSITY	Continuous COB
CUT INCREMENT	1.97-Inches (50mm), Field Cuttable
STRIP LIGHT WIDTH	0.47-Inches (12mm)
MOUNTING	3M™ VHB Double Sided Tape / Channels & Clips
COLOR TEMPERATURE	2100K / 2400K / 2700K / 3000K / Consult factory for additional CCT options
CRI	90+
COLOR CONSISTENCY	<5 SDCM (Standard Deviation Color Matching)
OPERATING VOLTAGE	24V DC
DIMMING	Forward / Reverse Phase and 0-10V
OPERATING TEMP.	-25° to 40°C (-13° to 104°F)
LIFE RATING	50,000 Hours @ 70% Lumen Maintenance
LISTINGS	
	cCSAus Listed to UL and CSA Standards IP67 Rated; Suitable for Wet Locations Declare Listed RoHS Compliant For use with Class 2 LED Drivers only
WARRANTY	
	Five (5) year replacement after date of purchase when installed within Mounting Channel Three (3) year replacement after date of purchase when installed without Mounting Channel

1. Approximate lumen output based on 3000K performance; see photometric test results for additional information

Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

ORDERING INFORMATION

FULL REELS

- Full Reels are available in Max Run Length for each available Wattage
- Each Reel has a 72-inch Plenum Rated Cable Power Lead soldered to the start of the length
- Additional lengths of Plenum Cable available (ordered separately)
- If field cut, use the included Silicone Endcaps with Silicone Sealant (TLAOSG) to re-seal the Strip Light
- Silicone Sealant (TLAOSG) and Plenum Rated Cable (CMP-2C) ordered separately; see Page 6 for details

Example Order: AFSSCN-530K-7-R

Series	Wattage	CCT¹/CRI	Location	Illuminated Length
AFSSCN Static White: Continuous COB	5 4.6W/Ft	90+ CRI 21K 2100K 24K 2400K 27K 2700K 30K 3000K	7 IP67 Wet Location	R Full Reel with 72-inch Power lead 4.6W/Ft: 16.4 Ft Reel


CUSTOM LENGTHS

- Custom Lengths cannot exceed the Maximum Run Length for the specified Wattage; see Max Run Length table on Page 10 for details
- Custom Lengths are factory sealed and bonded with specified Start of and End of Run Terminations
- If No Termination (NT) is specified for the End Termination, the end of the Strip Light will be sealed with an Endcap
- Allow additional lead time for Custom Lengths
- Custom Lengths are made-to-order and are not returnable; approved Submittal Sheets are required before processing the order

Example Order: AFSSCN-530K-7-S-NT-C188

Series	Wattage	CCT¹/CRI	Location	Start Termination	End Termination	Custom Length
AFSSCN Static White: Continuous COB	5 4.6W/Ft	90+ CRI 21K 2100K 24K 2400K 27K 2700K 30K 3000K	7 IP67 Wet Location	S² 72-inch Soldered Lead Wires SXXX² Custom Length Soldered Lead Wires	NT No Termination S² 72-inch Soldered Lead Wires SXXX² Custom Length Soldered Lead Wires	CXXX Custom Length Desired length is specified in inches i.e. if the desired length is 15 Ft.-8-Inches or 188-inches total, enter C188 AFSSCN Series has a cut increment of 1.97-inches, illuminated length will be rounded down to nearest cut increment

1. Consult factory for additional CCT options; allow additional lead time for special request CCTs  
2. All Lead Wires come sheathed in a Plenum Rated Cable rated to 90°C minimum; specify Custom Length Lead Wires in inches; max length: 120-inches



Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB


24V MOUNTING CHANNELS AND ACCESSORIES

- ALUMINUM MOUNTING CHANNEL**
  - Provides excellent heat sinking and protection to the LEDs while ensuring a clean, straight run
  - Anodized Satin Aluminum Channel
  - All Channels and Accessories are Declare Listed

**CHANNEL MOUNTING CLIPS**
  - Stainless Steel
  - 24-Inches between clips recommended for most applications
- CHANNEL ENDCAPS**
  - Creates a clean finish to the Mounting Channel
  - ABS Grey Plastic
  - Endcaps are ordered individually; one (1) solid Endcap and one (1) open Endcap (with Slot) is recommended
  - Use Endcaps with Slots for Power Feed

Channel, Lens, Endcaps, and Mounting Clips are ordered separately


WIDE SURFACE MOUNTING CHANNEL



Channel and Lens	
<b>AFEX1508S72-S</b>	6 Ft. Wide Surface Mounting Channel, Aluminum
<b>AFL1572-FR</b>	6 Ft. Wide Surface Channel Diffusion Lens, Frosted No Pixelation with Diffusion Lens

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor

EXTRA WIDE SURFACE MOUNTING CHANNEL



Channel and Lens	
<b>AFEX2011S72-S</b>	6 Ft. Extra Wide Surface Mounting Channel, Aluminum
<b>AFL2072-FR</b>	6 Ft. Extra Wide Surface Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Endcaps	
<b>AFEX2011S-EC</b>	Extra Wide Surface Channel Solid Endcap, Grey
<b>AFEX2011S-ECS</b>	Extra Wide Surface Channel Endcap with Slot, Grey

Mounting Clips	
<b>AFEX2011S-MC4</b>	Four (4) Mounting Clips, Stainless Steel

Specflex


Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

24V MOUNTING CHANNELS AND ACCESSORIES

45° ANGLED EXTRA WIDE MOUNTING CHANNEL



Channel and Lens	
<b>AFEX2030A72-S</b>	6 Ft. 45° Angled Extra Wide Mounting Channel, Aluminum
<b>AFL20A72-FR</b>	6 Ft. 45° Angled Extra Wide Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Endcaps	
<b>AFEX2030A-EC</b>	45° Angled Extra Wide Channel Solid Endcap, Grey
<b>AFEX2030A-ECS</b>	45° Angled Extra Wide Channel Endcap with Slot, Grey

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor

EXTRA WIDE RECESSED MOUNTING CHANNEL



Channel and Lens	
<b>AFEX2011R72-S</b>	6 Ft. Extra Wide Recessed Mounting Channel, Aluminum
<b>AFL2072-FR</b>	6 Ft. Extra Wide Recessed Channel Diffusion Lens, Frosted; No Pixelation with Diffusion Lens

Endcaps	
<b>AFEX2011R-EC</b>	Extra Wide Recessed Channel Solid Endcap, Grey
<b>AFEX2011R-ECS</b>	Extra Wide Recessed Channel Endcap with Slot, Grey

Mounting Clips not available; use 3M™ Double-Sided Adhesive or Screw and Wall Anchor

Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

24V CONNECTORS

TLCC Series

Barrel Connectors

- 6-Inch long Male and Female Connector
- Includes Wire Pigtail
- Hardwire to LED Driver for easy plug in connection

Model Number
<b>TLCCM</b> Male barrel connector
<b>TLCCF</b> Female barrel connector



TLCS Series

Plug-and-Play Power Splitter

- Approximately 2 feet long
- 2-Way: one (1) Male and two (2) Female Connectors
- 3-Way: one (1) Male and three (3) Female Connectors

Model Number
<b>TLCS2</b> Plug-and-play 2-way power splitter
<b>TLCS3</b> Plug-and-play 3-way power splitter



TLCEXT Series

Plug-and-Play Power Extension

- Select from 24-, 36-, 48- and 96-inch lengths
- Male Plug Connector on one end, Female Plug Connector on other

Model Number
<b>TLCEXT24</b> 24 Inch power extension
<b>TLCEXT36</b> 36 Inch power extension
<b>TLCEXT48</b> 48 Inch power extension
<b>TLCEXT96</b> 96 Inch power extension



Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

24V ACCESSORIES

Plenum Rated Cable

Two Conductor Plenum Rated Cable

Model Number			
CMP-2C-10	10Ft	CMP-2C-30	30Ft
CMP-2C-15	15Ft	CMP-2C-50	50Ft
CMP-2C-20	20Ft	CMP-2C-100	100Ft



Silicone Sealant

Wet Location Silicone Sealant

Model Number	
TLA0SG	Silicone Sealant



24V CONTROLLERS

TLPRTW

4-Channel Power Repeater

- Enables synchronized control of multiple runs from one controller
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPRTW	4-Channel Power Repeater (5-5/16" L x 1-3/4" W x 1-1/8" D)



TLPINT

DMX 512 CV Decoder

- Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others)
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPINT	DMX 512 CV Decoder (6-3/16" L x 3-1/8" W x 1-5/8" D)



TLPRGBRF

Dimming Controller with RF Remote Control

- Pre-programmed functions include: Color Strobe, 3- Channel Color Change and Gradual Brightness Change. Includes two (2) programmable presets
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use

Model Number	
TLPRGBRF	Dimming Controller w/ RF Remote Control (8-3/8" L x 1-5/8" W x 1-3/16" D)



Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

24V HARDWIRE LED DRIVERS

TLP24VHW Series

Hardwire Constant Voltage Driver

- 120VAC Input / 24VDC Output
- Includes stripped and tinned wire pigtails on the input and output sides
- 1 Foot Wire Leads
- Class 2 Recognized
- MUST BE MAINTAINED WITHIN AN ENCLOSURE THAT MEETS LOCAL BUILDING CODES AND NEC (SUPPLIED BY OTHERS)

Model Number
<b>TLP24VHW20</b> 20W (5-3/4" L x 1-1/2" W x 1-1/4" H)
<b>TLP24VHW60</b> 60W (6-1/3" L x 1-3/4" W x 1-1/4" H)
<b>TLP24VHW96</b> 96W (6-1/8" L x 2-3/8" W x 1-1/2" H)



L3D0 Series

Hi-lume™ 0.1% EcoSystem Voltage LED Driver with Soft-On, Fade to Black™

- 120-277VAC Input / 24VDC Output
- Enclosed Class 2 Listed Constant Voltage Driver
- 96W Max

Model Number
<b>L3D0-96W24V-U</b> 96W, 24V 120-277VAC (5.5" W x 2" H x 10.5" L)



TLP24VHW\*MVD-ENC Series

Hardwire Class 2 Constant Voltage Enclosed Driver

- 120-277VAC Input / 24VDC Output
- Class 2 Listed Constant Voltage UL Listed Enclosed LED Driver
- Forward/Reverse Phase and 0-10V Dimming
- 0-10V Dimming delivers smooth flicker free linear dimming down to 1% with most LEDs and a wide variety of compatible dimmers
- No minimum load requirement. Over voltage, current, temperature, and short-circuit protection.

Model Number
<b>TLP24VHW60MVD-ENC</b> 60W, Forward/Reverse Phase and 0-10V Dimming Driver (8" L x 3-3/8" W x 1-1/4" D)
<b>TLP24VHW100MVD-ENC</b> 96W, Forward/Reverse Phase and 0-10V Dimming Driver (8-1/4" L x 4-1/8" W x 1-1/2" D)



TLP24VHW\*MV-ENC & TLP24VHW\*MVD2-ENC Series

Hardwire Class 2 Constant Voltage Enclosed Driver

- 120-277VAC Input / 24VDC Output
- Class 2 Listed Constant Voltage UL Listed Enclosed LED Driver with built-in junction boxes; Wet Location Rated
- 0-10V Dimming and Non-dimming Models
- 0-10V Dimming Driver delivers smooth flicker free linear dimming down to 1% with most LEDs and a wide variety of compatible dimmers
- No minimum load requirement. Auto-reset protection for short circuit and over-temperature. Over load protection in CC mode.
- 12-1/8" L x 2-3/8" W x 1-3/8" D

Model Number
<b>TLP24VHW60MV-ENC</b> 60W, Non-dimming Driver
<b>TLP24VHW96MV-ENC</b> 96W, Non-dimming Driver
<b>TLP24VHW60MVD2-ENC</b> 60W, 0-10V Dimming Driver
<b>TLP24VHW96MVD2-ENC</b> 96W, 0-10V Dimming Driver



24V PLUG-IN POWER SUPPLIES

TLP24VP Series

Plug-and-Play Power Supply

- 120VAC Input / 24VDC Output
- Includes AC Wall Plug and Female Power Output Barrel Plug for easy installation
- Class 2 Listed

Model Number
<b>TLP24VP36</b> 36W (4-1/4" L x 2" W x 1-3/8" H)
<b>TLP24VP60</b> 60W (4-1/2" L x 2" W x 1-3/8" H)
<b>TLP24VP96</b> 96W (6-1/8" L x 2-3/8" W x 1-1/2" H)



**Specflex**  
Architectural Strip Lighting

## AFSSCN Wet Location Series

24V Static White, Continuous COB

## PRODUCT SPECIFICATIONS

## CONSTRUCTION

- Continuous Density Flex Strip: Continuous COB
- Encased in silicone sleeve, factory sealed and bonded
- 3-Ounce Copper Construction provides excellent heat dissipation and reduced voltage drop
- Full Reels have 72-inch Soldered Lead sheathed in a Plenum Rated Cable rated to 90°C min.

## LEDs

- **Color Temperature:**  
2100K, 2400K, 2700K, 3000K  
Consult factory for additional CCT options
- **CRI:**  
90+
- **Color Consistency:**  
<5 SDCM

## ELECTRICAL

- **Input Voltage:**  
24VDC
- **Average Power Consumption/Wattage:**  
4.6W per Foot
- **Dimming:**  
Forward / Reverse Phase and 0-10V Dimming
- **Ambient Operating Temp:**  
-25° to 40°C (-13° to 104°F)
- System designed and rated for 50,000 hours at 70% lumen maintenance
- Wet Location Rated Drivers and Controllers ordered separately

## INSTALLATION

- Includes 3M™ VHB Adhesive Backing for strong adhesion to channels and most smooth surfaces
- IP67 Rated Full Strip Light Reels include silicone mounting brackets and screws for low-profile installations
- If field cut, use the included Silicone Endcaps with Silicone Sealant (TLAOSG) to re-seal the Strip Light
- Wide selection of Aluminum Mounting Channels are available with or without a Lens, Lens sold separately
- Mounting Channels simplify installation and provide a uniform surface for strip adhesion and thermal management
- Channel Endcaps are available to create a finished appearance to the run; open or closed Endcaps are sold separately
- Mounting Clips available in packs of four (4); includes screws and dry-wall anchors for surface mounting, sold separately
- All Mounting Channels are field cuttable

## CERTIFICATIONS

- cCSAus Listed to UL and CSA Standards
- IP67 Rated, suitable for Wet Locations
- Declare Listed
- RoHS Compliant

## WARRANTY

- Covered by ConTech's full replacement guarantee after date of purchase:
  - Five (5) year replacement after date of purchase when installed within Mounting Channel
  - Three (3) year replacement after date of purchase when installed without Mounting Channel

# Declare.

**SpecFlex Architectural Striplight**  
**ConTech Lighting**

**Final Assembly:** Northbrook, Illinois, USA

**Life Expectancy:** 5 Year(s)

**End of Life Options:** Recyclable (35%), Landfill (65%)

**Ingredients:**

Aluminum; Copper; Carbonic acid, polymer with 4,4'-(1-methylethylidene)bis[pheno]; **Polyvinyl chloride**; **Vinyl fluoride-Vinylidene fluoride-Chlorotrifluoroethylene copolymer**; RTV silicone rubber; Ethylene glycol monomethyl ether; Tin, Organic; Plastiquinone; 1,3-Isobenzofurandione, polymer with 2,5-furandione and 2,2'-oxybis[ethano]; Gold; Titanium dioxide; Silver; Diethylene Glycol

### Living Building Challenge Criteria:

**I-13 Red List:**

- ☐ LBC Red List Free      % Disclosed: 100% at 100ppm  
☐ LBC Red List Approved      VOC Content: Not Applicable  
☒ Declared

I-10 Interior Performance: Not Applicable

**I-14 Responsible Sourcing:** Not Applicable

CNT-0004

EXP. 01 JUN 2025

Original Issue Date: 2024

MANUFACTURER RESPONSIBLE FOR LABEL ACCURACY  
INTERNATIONAL LIVING FUTURE INSTITUTE™ [living-future.org/declare](http://living-future.org/declare)



Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

PHOTOMETRICS



AFSSCN-530K-7: 24V Wet Location SpecFlex Static White Strip Light

4.6W/Ft, Continuous COB, 1-Foot Strip, 2983K, 91 CRI

Fixture Delivered Lumens: 390.2  
 Total Watts@24V: 5.0  
 Lumens Per Watt: 78.1  
 Center Beam Candle Power: 135  
 Beam Distribution: 111°  
 Spacing Criterion: 1.30

LM-63 Test No. G22050605  
 LM-79 Test No. S22050605

Intensity Distribution		
DISTANCE (FT.)	FOOTCANDLES (FC)	BEAM DIA. (FT.)
2 FT	33.8	5.8
4 FT	8.4	11.7
6 FT	3.8	17.5
8 FT	2.1	23.3
10 FT	1.4	29.1
12 FT	0.9	35.0




1. Colors Present within the Light Source

CCT MULTIPLIERS			
2400K	2700K	3000K	4000K
0.96	0.98	N/A	1.05

AFSSCN-530K-7 TM-30 DATA

ANSI/IES TM-30-18 Color Rendition Report Test No. S22050605

Colors are for visual orientation purposes only



Specflex

Architectural Strip Lighting

AFSSCN Wet Location Series

24V Static White, Continuous COB

DIMMING SPECIFICATIONS

LED Drivers have been tested with the following Dimmer Models:

TRIAC (LEADING EDGE) DIMMING

Manufacturer	Product	Model
Leviton	SureSlide	6672, 6674, 6674N, 66DF
	Decora Smart	D26HD, D2MSD, DN6HD
	Decora Digital	DDL06-1, DDM06, DDL06-1, DDMX1
	Decora Slide	DSL06, DSM10
	Illuminatech	IPL06
	Trimatron Rotary	RDL06, RNL06
	Toggle Slide	TSL06, TSM10
Lutron	Caseta	PD-6WCL
	Diva	DVCL-153P
	Lumea	LECL-153P
	Maestro	MACL-153M
	Skylark	SCL-153P
	Toggler	TGCL-153P

ELV (TRAILING EDGE) DIMMING

Manufacturer	Product	Model
Leviton	Decora Digital	DDE06
Lutron	Diva	DVELV-300P-WH
	Skylark	SELV-300P-WH

0-10V DIMMING

Manufacturer	Product	Model
Leviton	Illuminatech	IP710-DLX, IP710-LFZ
Lutron	Diva	DVSCSTV, DVSCTV, DVSTV, DVTV, DVTV-WH

- Testing has been performed on these Dimmers, but this does not imply any warranty of compatibility
- Dimming performance can be influenced by different Loads, as well as variations in Dimmer Switches within the same Model
- Dimmer Maximum Load Rating with LED may differ from published Traditional Source Dimmer Ratings; consult manufacturer for maximum dimmer information
- Consult factory for additional dimming information

MAX RUN LENGTH

INPUT = 24VDC

LED Driver	AFSSCN-5
Wattage	Max Run Length
20W	4 FT
36W	7 FT
60W	11 FT
96W	16 FT

- Max Run refers to the total single run of Strip Light that can go on a Driver
- Max Run Lengths are calculated with 24V DC at the start of the Strip Light run. Voltage drop may occur if not using proper wire gauge. Refer to the Voltage Drop and Wire Length Distance chart.
- Max Run lengths above are calculated with no more than 30% light loss from the start of the Strip Light run to the end of the Strip Light run for optimal light consistency. If run lengths are extended beyond the recommended lengths noted above, there will be inconsistent light output and voltage drop.
- Overall distance of Strip Light under load (lit length). If exceeded, damage to the Driver and Strip Light may result.

VOLTAGE DROP AND WIRE LENGTH DISTANCE

3% VOLTAGE DROP

Wire Gauge	20W	30W	36W	60W	96W
22 AWG	27 FT	18 FT	15 FT	9 FT	5 FT
20 AWG	43 FT	28 FT	24 FT	14 FT	9 FT
18 AWG	68 FT	45 FT	38 FT	23 FT	14 FT
16 AWG	109 FT	72 FT	60 FT	36 FT	23 FT
14 AWG	174 FT	115 FT	95 FT	57 FT	36 FT
12 AWG	272 FT	181 FT	151 FT	90 FT	57 FT
10 AWG	432 FT	288 FT	240 FT	144 FT	90 FT

The Voltage Drop/Wire Length Distance Chart provides general guidelines for determining wire gauge based on total load and distance from the Driver to the beginning of the Strip Light run.