

**SpecFlex**  
Architectural Strip Lighting | **24V Controllers**

**24V CONTROLLERS:** Compatible Accessories found on individual Specification Sheets

**TLPRTW**

*4-Channel Power Repeater*

- Enables synchronized control of multiple runs from one controller
- Not UL Listed for outdoor use
- Use with Non-dimming LED Drivers
- Use with 24V Static White, Monochrome, RGB or RGBW LED Strip Light

<b>Model Number</b>
<b>TLPRTW</b> 4-Channel Power Repeater (5-5/16" L x 1-3/4" W x 1-1/8" D)



**TLPRGBWRF**

*RGB/RGBW 28-Key Remote Controller*

- 8-Key RF Remote for color, speed, and brightness control
- Seven (7) programmable scenes
- 20AMP Max
- Use with Non-dimming LED Drivers
- Use with 24V RGB or RGBW LED Strip Light

<b>Model Number</b>
<b>TLPRGBWRF</b> 4-Channel Power Repeater (6-7/8" L x 1-3/4" W x 1-3/16" D)



**TLPINT**

*DMX 512 CV Decoder*

- Designed to convert universal DMX 512 signal to PWM signal when used with a DMX 512 console (by others)
- Not UL Listed for outdoor use
- Use with Non-dimming LED Drivers
- Use with 24V Static White, Monochrome, RGB or RGBW LED Strip Light

<b>Model Number</b>
<b>TLPINT</b> DMX 512 CV Decoder (6-3/16" L x 3-1/8" W x 1-5/8" D)



**TLPRGBWTC**

*RGB/RGBW Touch Controller*

- Dial Touch Controller, select color by using color wheel
- Speed and brightness control
- Pre-selected modes
- 20AMP Max
- Use with Non-dimming LED Drivers
- Use with 24V RGB or RGBW LED Strip Light

<b>Model Number</b>
<b>TLPRGBWTC</b> RGB/RGBW Touch Controller (6-7/8" L x 1-3/4" W x 1-3/16" D)



**TLPRGBRF**

*Dimming Controller with RF Remote Control*

- Pre-programmed functions include: Color Strobe, 3-Channel Color Change and Gradual Brightness Change. Includes two (2) programmable presets
- Use with Non-dimming LED Drivers
- Not UL Listed for outdoor use
- Use with 24V Static White, Monochrome, or RGB

<b>Model Number</b>
<b>TLPRGBRF</b> Dimming Controller w/ RF Remote Control (8-3/8" L x 1-5/8" W x 1-3/16" D)

