

## TLT STRIP LIGHT SERIES | 24V Controllers

### UNIVERSAL CONTROLLERS

#### TLPRTW

4-Channel Power Repeater

- Enables synchronized control of multiple runs from one controller
- 5-5/16" L x 1-3/4" W x 1-1/8" D
- For use with TLT Series Strip Light



Controller
<b>TLPRTW</b> 4-Channel Power Repeater

#### TLPRGBRF

Dimming Controller with RF Remote Control

- Pre-programmed functions include: Color Strobe, 3-Channel Color Change and Gradual Brightness Change
- Includes two (2) programmable presets
- Use with Non-Dimming Strip Light Power Supplies
- Not UL listed for outdoor use
- 8-3/8" L x 1-5/8" W x 1-3/16" D
- For use with TLT Series Strip Light



Controller
<b>TLPRGBRF</b> Dimming Controller with RF Remote Control

#### TLPINT

DMX 512 CV Decoder

- Designed to convert Universal DMX 512 Signal to PWM Signal when used with a DMX 512 Console (by others)
- Use with Non-Dimming Strip Light Power Supplies
- Not UL listed for outdoor use
- 6-3/16" L x 3-1/8" W x 1-5/8" D
- For use with TLT Series Strip Light



Controller
<b>TLPINT</b> DMX 512 CV Decoder

#### TLPI Series

IR Controllers

- **TLPICB: IR Cabinet Switch**  
Allows on/off switching functionality for use with cabinet doors
- **TLPIWV: IR Wireless Waving Switch**  
Allows on/off switching functionality by waving an object within the IR Field
- 72W Max.
- 1-1/2" L x 1-3/16" W x 5/16" H
- For use with TLT Series Strip Light



IR Controller
<b>TLPICB</b> IR Cabinet Switch
<b>TLPIWV</b> IR Wireless Waving Switch

### STATIC WHITE/STATIC COLOR CONTROLLERS

#### TLPDIM10V

0-10V Dimming Module

- For use with standard 0-10V Dimmers
- Dimming down to 15%
- Use with Non-Dimming Strip Light Power Supplies
- Not UL listed for outdoor use
- 4-3/4" L x 1-1/2" W x 1-1/2" D
- For use with TLT Series Static White and Static Color Strip Light



Controller
<b>TLPDIM10V</b> Static Color 0-10V Dimming Module

#### TLPIDM

Strip Light Touch Dimmer

- Allows adjustment of the brightness of the LEDs by touching the Controller housing
- 72W Max.
- 1-1/2" L x 1-3/16" W x 5/16" H
- For use with TLT Series Static White and Static Color Strip Light



Controller
<b>TLPIDM</b> Strip Light Touch Dimmer

## TLT STRIP LIGHT SERIES | 24V Controllers

### RGB/RGBW CONTROLLERS

#### TLPRGBWTC

*Touch Controller*

- Dial Touch Controller: select color by using color wheel
- Speed and brightness control
- Pre-selected modes
- 20AMP Max.
- 6-7/8" L x 1-3/4" W x 1-3/16" D
- For use with TLT RGB/RGBW Series Strip Light



Controller
<b>TLPRGBWTC</b> Touch Controller

#### TLPRGBWRF

*28-Key Remote Controller*

- 8-Key RF Remote for color, speed, and brightness control
- Seven (7) programmable scenes
- 20AMP Max.
- 6-7/8" L x 1-3/4" W x 1-3/16" D
- For use with TLT RGB/RGBW Series Strip Light



Controller
<b>TLPRGBRF</b> Dimming Controller with RF Remote Control

### RGB/RGBW CONTROLLERS

#### TLPTWMT

*Touch Controller*

- Dial Touch Controller, select color temperature by color circle
- Speed and brightness control
- Receiver power input 12-24VDC
- Max current load 9A (3Ax3 Channels)
- Max output power 216W
- 5-5/16" L x 1-3/16" W x 7/8" H
- Remote:  
Frequency: 433.92MHz  
Dimensions: 4-1/8" L x 2-1/4" W x 3/8" H
- For use with TLT Tunable White (TW) Series Strip Light



Controller
<b>TLPTWMT</b> Touch Controller

#### TLPTW2RF

*Premium Controller*

- Premium RF Remote with push button control for color temperature, speed and brightness
- Pre-programmed scenes and two (2) programmable scenes
- Receiver power input: 12-24VDC
- Max current load: 12A (3A x four (4) Channels)
- Max output power: 288W
- 5" L x 1-3/8" W x 7/8" H
- Remote  
Frequency: 2.4GHz  
Dimensions: 5-3/4" L x 1-5/8" W x 1/2" H
- For use with TLT Tunable White (TW) Series Strip Light



Controller
<b>TLPTW2RF</b> Premium Controller